


# PanaSync™ E70i



- 17" Multi-mode Color Display (VIS 16.0")
- 1,280 x 1,024 Maximum Resolution NI
- .27mm Dot Pitch
- Crystal Pigment
- Advanced AGRAS™ Coating
- ENERGY STAR® Compliant
- On-screen Adjustment Menu
- 3 Year Limited Warranty
- 1 Year "On-Site" Replacement

As an ENERGY STAR® partner, Panasonic Computer Peripheral Company has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. All product/brand names are trademarks or registered trademarks of their respective holders. Specifications and designs are subject to change without notice. Product may be subject to export control regulations. Copyright ©1999 Matsushita Electric Corporation of America. All rights reserved.

## O n l i n e   S p e c   S h e e t

	Panasonic Digital Imaging Company Unit of Matsushita Electric Corporation of America Computer Peripherals Division Headquarters 2 Panasonic Way, Secaucus, NJ 07094
---	--

www.panasonic.com/office

## PanaSync™ E70i Specifications

<b>CRT Screen Size</b>	17" CRT (16.0"/40.6 cm Viewable Image Size) Flat-Square
<b>Dot Pitch</b>	0.27 mm
<b>Surface</b>	Advanced AGRAS™ Coat
<b>Viewable Display Area (HxV)</b>	
<b>Factory Preset</b>	11.81" x 8.86", 14.8" diagonal at 1,024 x 768 75 Hz NI
<b>Full Scan</b>	12.80" x 9.60", 16.0" diagonal (Typical)
<b>Input</b>	
<b>Video Signal</b>	RGB Analog (0.7 Vp-pm 1.0 Vp-p, 75 ohms)
<b>Sync Signal</b>	H/V separate (TTL), H/V combined
<b>H-sync</b>	30 - 70 kHz
<b>V-Sync</b>	50 - 160 Hz
<b>Modes</b>	1 Factory Preset, 7 Reservations, 13 User Memories
<b>Connectors &amp; Cables</b>	
<b>Video Input</b>	One 15-pin mini D-sub on attached cable (4.92'/1.5 meters)
<b>Power</b>	One UL 3-pole (CEE 22 type) (5.91'/1.8 meters)
<b>Controls</b>	
<b>Front Panel</b>	1 key, Left key, Right key, 2 key, Power Switch (On/Off)
<b>On-Screen Display</b>	Contrast, Brightness, H. Position, H. Size, V. Position, V. Size, V. Pincushion, V. Pincushion Balance, Trapezoid, Parallelogram, Color Temperature (9,300 + 8 MPCD/7500K/6500K/5000K/User Color), Recall (Factory Setting), Video Level (0.7/1.0 V p-p), Language (English, French, German, Spanish & Italian), (OSD Position (6 positions)) Degauss, Tilt (Rotation), Display Frequency (0.7/1.0 V p-p), Monitor Self-Test (w/no Signal Input)
<b>Video Bandwith</b>	108 MHz (Typical)
<b>Resolution (HxV)</b>	1,280 dots x 1,024 lines 60 Hz NI, FCC Class B, Max. 1,280 dots x 1,024 lines 66 Hz NI, FCC Class A, Max.*
<b>Operating Conditions</b>	
<b>Temperature</b>	41-95°F
<b>Humidity</b>	5%-90% Non-condensing
<b>Dimensions</b>	15.94" (W) x 15.93" (H) x 16.73" (D)
<b>Weight</b>	34.76 lbs
<b>Approvals</b>	UL1950, CSA 22.2 No. 950, DHHS, 21CFR Subchapter J, HC(HWC), MPR II, VESA DPMS/ENERGY STAR®
<b>Power Consumption</b>	
<b>Supply</b>	90 to 132 V AC (50 or 60 Hz)
<b>On</b>	95 Watts (Typical)
<b>Stand-by</b>	15 Watts
<b>Suspend</b>	15 Watts
<b>Off State</b>	4.5 Watts
<b>Off</b>	0 Watts
<b>Warranty</b>	3-Year Limited Parts & Labor, 1-Year On-Site Replacement (see your dealer for details)
<b>Other</b>	Windows 95 Plug & Play

\*This monitor may only be used in a commercial, business or industrial environment at resolutions above 1,280 x 1,024 60 Hz.