

HARDWARE INSTALLATION

The Adaptec AHA-1520/1522 AT-to-SCSI Host Adapter has been designed to operate as shipped in the majority of AT class computers. The host adapter's factory default settings should remain in their original positions. The AHA-1520/1522 is shipped with the following factory default settings:

SCSI Disconnection	Enabled
SCSI Address	7
SCSI Parity	Enabled
Terminators	Installed
Terminator Power	Supplying
Synchronous Negot.	Enabled
DMA Channel	0
Interrupt Channel	11
AT Port Address	340h
AT BIOS Address	DCOOOH, Enabled
FD Controller	Enabled (AHA-1522)
Data Transfer Mode	Programmed I/O

To Perform Installation:

TURN OFF POWER TO THE SYSTEM AND EXTERNAL EQUIPMENT.

Remove the cover of your AT personal computer that exposes the AT bus slots.

Locate an unused AT expansion slot in your AT system. AT-type slots can be recognized by the fact that they have two physical edge connectors, one 62-pin and the other 36-pin, in line with one another.

Remove the corresponding system expansion slot cover by turning the screw that secures it from the top counterclockwise.

Align the AT I/O Bus Connector on the bottom of the AHA-1520/1522 into this AT slot. Use the screw from the corresponding expansion slot cover to secure the AHA-

system frame. The host adapter and the external or external connector orientation is maintained

first or the last unit at- with internal and external the SCSI terminators from

the reverse order.

SN	Use this pin pair to enable or disable synchronous negotiation. No jumper = syn. neg. off; *Jumper = syn. neg. on
DN	Use this pin pair to enable and disable disconnection by the target SCSI device. No jumper = disconnect disallowed; *jumper = disconnect allowed
R	Not used


*denotes default configuration

Jumper Configuration Reference

Five jumper blocks are located on the board to configure user-selectable options. A black bar represents a jumper installed. It should not be necessary to change the jumper settings.

Jumper Block J5 (Data)

Default settings of jumper block J5:



Pin Pair	Description
DT	Use this pin pair to choose whether data transfer will be performed in PIO or 2nd-party DMA mode. *No jumper = PIO; Jumper = 2nd-party DMA
BT	Use this pin pair to choose whether the host adapter BIOS performs the boot operation. No jumper = Disable booting from SCSI disk drive; Jumper = Boot from SCSI disk drive.
M0, M1	Use these pin pairs to select which types of messages you want the AHA-1520/1522 to display when you boot your computer. *1. No jumper M0, no jumper M1 = Adaptec header display and error messages 2. No jumper M0, jumper M1 = Adaptec header display, boot progress and error messages 3. Jumper M0, no jumper M1 = SCSI device information, jumper configuration, boot progress, and error messages 4. Jumper M0, jumper M1 = Error messages

1520/1522's bracket to your A


Attach the SCSI Bus to the host peripherals, using either the internal connector, making sure that pin 1 is throughout the bus.

If the host adapter is not the first attached to the cable (e.g., boot connectors are used), remove the host adapter.

Reassemble the PC system in


Jumper Block J6 (Channel Selection and SCSI ID)

The following diagram shows the default settings of jumper block J6:




Pin Pair **Description**


SD Use the three pin pairs marked SD to determine the SCSI ID of the host adapter.



IC Use the two pin pairs marked IC to select the host adapter REQ channel. You must also use pin pairs I0, I1, I2, and I9 on jumper block J9 to select an IRQ channel.



DC The two pin pairs marked DC to select the host adapter DMA channel. Only DMA channel 0 is supported.



SP Parity checking enabled or disabled.
 *No jumper = parity enabled; Jumper = parity disabled.

**denotes default configuration*

Jumper Block J7 (Floppy Drive Options) – AHA-1522 Only


The following diagram shows the default settings of jumper block J7:



Pin Pair **Description**

FE Use this pin pair to determine whether the floppy controller on the host adapter is enabled or disabled.
 *Jumper = floppy enabled (default); No jumper = floppy disabled.

DR, DA Use the four pin pairs marked DR and DA to set the floppy DMA request channel.




I6, I0 Set Floppy IRQ Channel.
 *Jumper I6 = Interrupt Channel 6 enabled;
 Jumper I0 = Interrupt Channel 10 enabled.

DS Set to support floppy drive with dual speed spindle.
 *No jumper = disabled; Jumper = enabled.

**denotes default configuration.*

Jumper Block J8 (DMA Request & Acknowledge Channel)


Note that the DMA channel is also controller by jumper block J6. The following diagram shows the default settings of jumper block J8:




Pin Pair	Description
D0, D0	When jumpers are installed on D0, D0, it selects DMA channel 0. The other J8 jumper options are reserved.

Jumper Block J9 (IRQ Channel, Port Address, and BIOS)

The following diagram shows the default settings of jumper block J9:




Pin Pair	Description
I2, I1, I0, I9	Use these four pin pairs to select the IRQ channel. You must also select the corresponding interrupt channel with the IC pin pairs on jumper block J6. Jumper I2 = IRQ 12 *Jumper I1 = IRQ 11 (Default) Jumper I0 = IRQ 10 Jumper I9 = IRQ 9 (not recommended with Windows 3.0)
AL	Select port address range. No jumper = 340-35E (hex); Jumper = 140-15E (hex)
J6, J4	Select BIOS address location.



BE	Select host adapter BIOS enable. *Jumper = Boot from SCSI disk enabled; No jumper = boot from SCSI disk disabled.
----	----------------------------------------------------------------------------------------------------------------------

*denotes default configuration



DEFAULT SETTINGS AND REFERENCE DIAGRAM

TERMINATORS

Terminators

The SCSI bus must also be terminated correctly to ensure proper operation. The first and last physical SCSI devices on the SCSI cable must have terminators installed. All other SCSI devices must have terminators removed. The AHA-1520/1522 host adapter is usually the first device on the SCSI Bus and has terminators installed at the factory.

SOFTWARE INSTALLATION

Copy the files from the ASW-1210 Program diskette to the root directory of drive C using the DOS COPY command. In order for the ASPI DOS Manager files to be loaded whenever the system is booted, the CONFIG.SYS file must contain the following DEVICE= commands:

```
DEVICE = ASPI2DOS.SYS
DEVICE = ASPIDISK.SYS
```

Using any ASCII file editor, add the individual device driver commands to an existing CONFIG.SYS file, or follow the instructions in the DOS Operations Reference Manual to create a new CONFIG.SYS file. FAILURE TO LOAD ALL THE DEVICE DRIVERS IN THE CORRECT ORDER CAUSES THE PROGRAM TO NOT BE INSTALLED. The following command line options may be added to the device drivers in the CONFIG.SYS file. (Refer to the User's Manual for details or the ASW-1210 Installation Guide.)

```
DEVICE = ASPI2DOS.SYS [/D] * [/P<port address>]
[/L] [/C or /C-] [/TD or /TP] [/Y or /Y-]
[/U or /U-], * [/A<DMA channel>]
[/H<HA SCSI ID>] * [/Q<interrupt channel>] [/L]
[/I] [/Z]
```

```
DEVICE = ASPIDISK.SYS [/D] [/R<number of
logical drives>]
```

*Host adapter must be jumpered accordingly.

DOS provides access to physical hard disk drives C and D. You must use the DOS FDISK and **Format** programs for drives C and D. DO NOT use AFDISK with drive C and D. To use a hard disk partitioned by AFDISK as drive C or D, you should install that hard disk under the host adapter BIOS by changing the drive SCSI ID to 0 or 1.

When starting AFDISK program, it must be run from the root directory of drive C or the AFDISK directory if an AFDISK directory was created. When ready, type:

AFDISK (at the DOS prompt)

and press ENTER. The AFDISK utility is menu driven. Follow the directions on the screen to partition and format the selected SCSI devices including removable media. The AFDISK utility also includes an on-line **HELP** file which is accessed by pressing the **F1** key. The AFDISK may be exited at any time without executing by pressing the **ESC** key.

When the SCSI device(s) are successfully partitioned and formatted, reboot the system. This saves any changes made and allows use of the newly installed disk(s) or partitions(s). The new partitions will be installed with the ASPIDISK.SYS driver.

F.C.C. CERTIFICATION

This equipment generates and uses radio frequency, and if not installed and used properly, that is, in strict accordance with the manufacturer's instructions, may cause interference to radio and television reception. It has been type-tested and found to comply with the limits for a Class B computing device in accordance with the specifications in "Subpart J of Part 15 of FCC Rules", which are designed to provide reasonable protection against such interference in a residential installation. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient receiving antenna.
- Relocate the computer with respect to the receiver.
- Move the computer away from the receiver.
- Plug the computer into a different outlet so that computer and receiver are on different branch circuits.

If necessary, the user should consult the dealer or an experienced radio/television technician for additional suggestions. The user may find the following booklet prepared by the Federal Communications Commission helpful.

"How to Identify and Resolve Radio-TV Interference Problems." This booklet is available from the U.S. Government Printing Office, Washington, D.C. 20402. Stock No. 004-000-00345-4.

COPYRIGHT

© Copyright 1990 by Adaptec, Inc. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written consent of Adaptec, Inc., 691 South Milpitas Blvd., Milpitas, California 95035.

CHANGES

The material in this guide is for information only and is subject to change without notice. Adaptec reserves the right to make changes in the product design without reservation and without notification to its users.

Details are available in the AHA-1520/1522 User's Manual. Questions can be answered via the Adaptec Bulletin Board (8 data bits, 1 stop bit, no parity, 1200 or 2400 baud) at: **(408) 945-7727**.

adaptec • 691 south milpitas blvd. • milpitas, california • 95035

Stock No.: 510096-00 Rev B TH 5/91

SOFTWARE INSTALLATION

Copy the files from the ASW-1210 Program diskette to the root directory of drive C using the MS-DOS COPY command. In order for the ASPI MS-DOS Manager files to be loaded whenever the system is booted, the CONFIG.SYS file must contain the following DEVICE= commands:

DEVICE = ASP12DOS.SYS
DEVICE = ASPI2DISK.SYS

Using any ASCII file editor, add the individual device driver commands to an existing CONFIG.SYS file, or follow the instructions in the MS-DOS Operations Reference Manual to create a new CONFIG.SYS file. FAILURE TO LOAD ALL THE DEVICE DRIVERS IN THE CORRECT ORDER, CAUSES THE PROGRAM TO NOT BE INSTALLED. The following command line options may be added to the device drivers in the CONFIG.SYS file. (Refer to the User's Manual for details.)

DEVICE = ASP12DOS.SYS (/D) (/P<port address>) (/V) (/W) (/X<speeds>) (/N<bus on time>) (/F<bus off time>) (/I).

MS-DOS provides access to physical hard disk drives C and D. You must use the MS-DOS FDISK and **Format** programs for drives C and D. DO NOT use AFDISK with drive C and D. To use a hard disk partitioned by AFDISK as drive C or D, you must use AFDISK to delete the partitions, and then use MS-DOS **FDISK** to create new partitions.

When starting AFDISK program, it must be run from the root directory of drive C or the AFDISK directory if an AFDISK directory was created. When ready, type:

AFDISK (at the DOS prompt)

and press ENTER. The AFDISK utility is menu driven. Follow the directions on the screen to partition and format the selected SCSI devices. The AFDISK utility also includes an on-line **HELP** file which is accessed by pressing the **F1** key. The AFDISK may be exited at any time without executing by pressing the ESC key.

When the SCSI device(s) are successfully partitioned and formatted, reboot the system. This saves any changes made and allows use of the newly installed disk(s) or partition(s).

F.C.C. CERTIFICATION

This equipment generates and uses radio frequency, and if not installed and used properly, that is, in strict accordance with the manufacturer's instructions, may cause interference to radio and television reception. It has been type-tested and found to comply with the limits for a Class B computing device in accordance with the specifications in 'Subpart J of Part 15 of FCC Rules', which are designed to provide reasonable protection against such interference in a residential installation. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient receiving antenna.
- Relocate the computer with respect to the receiver.
- Move the computer away from the receiver.
- Plug the computer into a different outlet so that computer and receiver are on different branch circuits.

If necessary, the user should consult the dealer or an experienced radio/television technician for additional suggestions. The user may find the following booklet prepared by the Federal Communications Commission helpful.

'How to Identify and Resolve Radio-TV Interference Problems.' This booklet is available from the U.S. Government Printing Office, Washington, D.C. 20402. Stock No. 004-000-003345-4.

COPYRIGHT

© Copyright 1990 by Adaptec, Inc. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written consent of Adaptec, Inc., 691 South Milpitas Blvd., Milpitas, California 95035.

FIVE-YEAR LIMITED LIFE-TIME WARRANTY

The Seller warrants that the products to be delivered under this purchase order will be free from defects in material and workmanship under normal use and service. Seller's obligations under this Warranty are limited, at its sole option, to: (i) replacing or (ii) repairing or (iii) giving credit for, any such products which shall, within five (5) years from date of shipment, be returned to the Seller's factory, transportation charges prepaid, and which are, after examination, disclosed to the Seller's satisfaction to be thus defective. THIS WARRANTY IS EXPRESSED IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED, STATUTORY, OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND OF ALL OTHER OBLIGATIONS OR LIABILITIES ON THE SELLER'S PART, AND IT NEITHER ASSUMES NOR AUTHORIZES ANY OTHER PERSON TO ASSUME FOR THE SELLER ANY OTHER LIABILITIES IN CONNECTION WITH THE SALE OF THE SAID ARTICLES. This warranty shall not apply to any of such products which shall have been repaired or altered, except by the Seller, or which shall have been subjected to misuse, negligence, or accident. The aforementioned provisions do not extend the original warranty period of any product which has either been repaired or replaced by Seller. Prior to returning any products to Seller, Buyer must request and obtain a Return Material Authorization (RMA).

CHANGES

The material in this guide is for information only and is subject to change without notice. Adaptec reserves the right to make changes in the product design without reservation and without notification to its users.

Details are available in the AHA-152X User's Manual. Questions can be answered via the Adaptec Bulletin Board (8 data bits, 1 stop bit, no parity, 1200 or 2400 baud) at: **(408) 945-7177**.

adaptec, 691 south milpitas Blvd, milpitas, california 95035

510096-00 TH 3/90

adaptec

AHA-1520/22 Installation Guide

FILE COPY

HARDWARE RE INSTALLATION

The Adapter, AHA-152X AT-to-SCSI Host Adapter has been designed to operate as shipped in the majority of settings shown below. The host adapter's factory default settings remain in their original positions. The AHA-152X is shipped with the following factory default settings:

- SCSI Disconnect: Enabled
- SCSI Address Selection: 7
- SCSI Parity: Disabled
- Terminators: Installed
- Terminator Polarity: Supplying
- Synchronous Negotiation: Enabled
- DMA Channel Negotiation: 0
- Interrupt Channel: 1, 1
- AT Port Address: 340h
- AT BIOS Address: DCC000h, Enabled
- FD Controller Address: Enabled (AHA-1522)
- Data Transfer Mode: PIO

To Perform Installation:

1. TURN OFF POWER TO THE SYSTEM AND EXTERNAL EQUIPMENT.
2. Remove the cover of your AT personal computer that exposes the AT bus slots.
3. Locate an unused AT bus slot.
4. Type slots can be used for AT expansion slot in your AT system. AT type slots are not recognized by the fact that they have 36-pin, in-line connectors, one 62-pin and the other with one another.
5. Remove the expansion system expansion slot cover by turning the corresponding system expansion slot cover clockwise. The screw that secures it from the top counter-clockwise.
6. Align the AT Bus Connector on the bottom of the AHA-152X in the AT Bus Connector on the bottom of the expansion slot. Use the screw from the AHA-152X's bracket to your expansion slot cover to secure the AHA-152X's AT system frame.
7. Attach the SCSI Bus to the host adapter and the peripheral, using the internal or external connector, making sure the internal or external connector, out the bus connector orientation is maintained throughout the host adapter.
8. If the host adapter is not the first or the last unit in the cable, remove the SCSI terminators from the board.
9. Reassemble the system in the reverse order.

Jumper Configuration Reference

Five sets of jumpers are located on the board to configure user-selectable options. Jumpers installed at the factory are shown as "X". Those not installed are shown as "o". It should not be necessary to change the jumper settings.

J5—General Control

- | | | | | | | | |
|--------------------------|-------------------------------------|--------------------------|--------------------------|-------------------------------------|--------------------------|--------------------------|--------------------------|
| Pin 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

- 1—Data Transfer in DMA
- 2—Boot Enable (Intercept INT19 call)
- 3,4—Message—Allow a combination of:
 - Adapter Header (default)
 - Jumper Config. Information
 - SCSI Device Information
 - Boot Progress Report
 - Error Messages (default)
- 5—Synchronous Negotiation Enable
- 6—Disconnect/Reconnect enable for target
- 7,8—(Reserved)

J6 SCSI Selection

- | | | | | | | | |
|-------------------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|-------------------------------------|
| Pin 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> |

- 1,2,3—SCSI ID (Set in binary 0-7)
- 4,5—Interrupt Channel Select (9 thru 12)
- 6,7—DMA Channel Select (Coded 0,5,6,7)
- 8—SCSI Parity Disable

J7 Floppy Disk Selection (AHA-1522 only)

- | | | | | | | | |
|-------------------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|--------------------------|
| Pin 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

- 1—FLOPPY Enable
- 2—DMA REQ 2 Select
- 3—DMA REQ 3 Select
- 4—DMA ACK 2 Select
- 5—DMA ACK 3 Select
- 6—INT Request 6 Select
- 7—INT Request 10 Select
- 8—DUAL SPEED Enable

J8 DMA Selection


- | | | |
|--------------------------|--------------------------|--------------------------|
| Pin 1 | 2 | 3 |
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

- 1—DMA REQ 7 Se
- 2—DMA REQ 6 Se
- 3—DMA REQ 5 Se
- 4—DMA REQ 0 Se
- 5—DMA ACK 7 Se
- 6—DMA ACK 6 Se
- 7—DMA ACK 5 Se
- 8—DMA ACK 0 Se

J9 Interrupt Select

- | | | |
|--------------------------|-------------------------------------|--------------------------|
| Pin 1 | 2 | 3 |
| <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |

- 1—Interrupt Requ
- 2—Interrupt Requ
- 3—Interrupt Requ
- 4—Interrupt Requ
- 5—PRIMARY/Sec
- 6,7—BIOS Address
- 8—BIOS Enable



DEFAULT SETTINGS

Terminators

The SCSI bus must ensure proper operation of SCSI devices on the installed. All other terminators removed. The first device or installed at the fa