

HP-UX - Single Server FCAL

HSG80 – Single Controller Rackmount – Dual Connections (Active,Active)

Rack Mount Version

Includes: Integrated BA370 Backplane with **universal RETMA and METRIC mounting**; single HSG80 controller with 64 MB cache; single cache battery in SBB with cable; five shelf power supplies optionally expandable to eight; fully redundant cooling; Environmental Monitor Unit (EMU); 2U battery shelf, 5-meter host connection cable; power cord and GLMs.

Step1 – Select RM

Description	Compaq
-------------	--------

Tip: Choose one

RM RA8000 Sing. Cntrl.	380660-B21
------------------------	------------

Tip: Choose up to two, each supports 24 drives: Optional

Expansion Rack	380568-B21
----------------	------------

Note: Exp. rack includes RETMA/METRIC mounting hardware

Tip: Choose one per Expansion Rack

Expansion Cable Kit	380563-001
---------------------	------------

Note: For Customer Requiring a Cab...see Step 7

Redundant Power Options: Optional

Description	Compaq
-------------	--------

Tip: Choose up to three per BA370 enclosure

180 Watt Power supply	380565-B21
-----------------------	------------

Tip: Choose one per BA370 enclosure

AC Input Unit	380564-B21
---------------	------------

Tip: Order one per AC Input Unit ordered

AC Pwr Cord	103541-001
-------------	------------

Cache Upgrades – Optional

Note: 64, 128, 256 or 512MB supported only...four slots available for cache...all slots must be of like size DIMMS

Description	Compaq
-------------	--------

Tip: RA8000 Choose One (RA8000 comes with 64MB)

64MB – 2x32MB	380673-B21
---------------	------------

Tip: for 256MB or 512MB remove 64MB DIMM and order quantity accordingly

256MB – 2x128MB	380674-B21
-----------------	------------

Step2 – ACS – Firmware (PCMCIA) Card

Tip: One per HSG80 required.

Description	Compaq
-------------	--------

ACS v8.3	380577-001
----------	------------

Step3 – Platform Kit

Note: Includes SWCC

Tip: One per OS type required

Description	Compaq
HP-UX	380557-001

Step4 – Host Adapter

Note: GLM included

Tip: Only one adapter is required.

Description	Compaq
A3404A (HSC bus, K-Class)	(Must Be Ordered From Manufacturer)
A3591A (HSC bus, D-Class)	(Must Be Ordered From Manufacturer)

Step5 - Disks

Description	Compaq
4GB, 7200 RPM, UWSE	380691-B21
9GB, 7200 RPM, UWSE	DS-RZ1DA-VW
9GB, 10K RPM, UWSE	380588-B21
18GB, 7200 RPM, UWSE	DS-RZ1EA-VW
18GB, 10K RPM, UWSE	380589-B21

Step6 – Hub, GBIC's and Cables

Note: Hub required...point to point not supported...(no GBIC's included)

HUB

Description	Compaq
12 Port Hub	295573-B22

GBIC and Connection Kit

Tip: Configure one kit for this config.

Description	Compaq
3 GBIC + 2 – 2M Cables	380579-B21

CABLES - Optional

Tip: One 5M cable/controller comes with RA8000 and two 2M cables come with the GBIC Kit.

Description	Compaq
2Meter	234457-B21
5Meter	234457-B22
15Meter	234457-B23
30Meter	234457-B24
50Meter	234457-B25

Step7 – Cabinets Empty

Digital Classic H9A15 Type Cab (41U) with side panels and doors:

Description	Compaq
41U RETMA Cab Blue	380586-B21
41U RETMA Cab Opal	380586-B22
<i>Note: PDU Required:</i>	
PDU 60Hz	380582-001 or -B21

Optional: If joining multiple cabs:

Joiner Kit Blue	380584-B21
Joiner Kit Opal	380584-B22
Filler	380585-B21

Compaq Classic 42U RETMA Cab: includes front and rear Plexiglas doors.

Description	Compaq
42U RETMA Cab	165753-001

Note: The following parts do not come with cabinet

Side panel	165652-001
Stabilizing feet	189907-001
Coupling Kit	165664-001
PDU DOM Low	295363-001

Note: 110 Volts – L5-30P plug

PDU DOM High	295363-002
--------------	------------

Note: 208/240 Volts – L6-20P plug

Note: One PDU required per Cab...order High or Low Voltage based on customers electrical requirements...when redundancy is required order second PDU.

Step8 – UPS

Description	Compaq
Low Voltage R3000	242705-001

Note: Actual VA is 2880...uses L5-30P plug

High Voltage R3000h	242705-003
---------------------	------------

Note: Actual VA is 3000...uses L6-20P plug