



# Sun StorEdge™ 5210 and 5310 NAS Appliance and Gateway System Release Notes

---

Sun Microsystems, Inc.  
[www.sun.com](http://www.sun.com)

Part No. 819-2857-12  
November 2005, Revision A

Submit comments about this document at: <http://www.sun.com/hwdocs/feedback>

Copyright 2005 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, U.S.A. All rights reserved.

Sun Microsystems, Inc. has intellectual property rights relating to technology that is described in this document. In particular, and without limitation, these intellectual property rights may include one or more of the U.S. patents listed at <http://www.sun.com/patents> and one or more additional patents or pending patent applications in the U.S. and in other countries.

This document and the product to which it pertains are distributed under licenses restricting their use, copying, distribution, and decompilation. No part of the product or of this document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any.

Third-party software, including font technology, is copyrighted and licensed from Sun suppliers.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and in other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, Java, AnswerBook2, docs.sun.com, Sun StorEdge, Java, and Solaris are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and in other countries.

All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and in other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

U.S. Government Rights—Commercial use. Government users are subject to the Sun Microsystems, Inc. standard license agreement and applicable provisions of the FAR and its supplements.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

---

Copyright 2005 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, Californie 95054, Etats-Unis. Tous droits réservés.

Sun Microsystems, Inc. a les droits de propriété intellectuels relatants à la technologie qui est décrit dans ce document. En particulier, et sans la limitation, ces droits de propriété intellectuels peuvent inclure un ou plus des brevets américains énumérés à <http://www.sun.com/patents> et un ou les brevets plus supplémentaires ou les applications de brevet en attente dans les Etats-Unis et dans les autres pays.

Ce produit ou document est protégé par un copyright et distribué avec des licences qui en restreignent l'utilisation, la copie, la distribution, et la décompilation. Aucune partie de ce produit ou document ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y en a.

Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Des parties de ce produit pourront être dérivées des systèmes Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, Java, AnswerBook2, docs.sun.com, Sun StorEdge, Java, et Solaris sont des marques de fabrique ou des marques déposées de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays.

Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

L'interface d'utilisation graphique OPEN LOOK et Sun™ a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciées de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

LA DOCUMENTATION EST FOURNIE "EN L'ÉTAT" ET TOUTES AUTRES CONDITIONS, DECLARATIONS ET GARANTIES EXPRESSES OU TACITES SONT FORMELLEMENT EXCLUES, DANS LA MESURE AUTORISEE PAR LA LOI APPLICABLE, Y COMPRIS NOTAMMENT TOUTE GARANTIE IMPLICITE RELATIVE A LA QUALITE MARCHANDE, A L'APTITUDE A UNE UTILISATION PARTICULIERE OU A L'ABSENCE DE CONTREFAÇON.



Please  
Recycle



Adobe PostScript

# Contents

---

|  |          |
|--|----------|
| <b>Sun StorEdge 5210 and 5310 NAS Appliance and Gateway System Release Notes</b> | <b>1</b> |
| System Requirements  | 2        |
| Software Updates   | 3        |
| New Features   | 3        |
| Resolved Issues  | 5        |
| Known Issues   | 7        |
| Cluster-Specific Issues (Sun StorEdge 5310 Cluster Only)                         | 9        |
| File Replicator-Specific Issues  | 11       |
| Gateway-Specific Issues (Sun StorEdge 5310 Gateway System Only)                  | 12       |
| Addenda to the Documentation   | 12       |
| Upgrading Array and Drive Firmware Revision Levels                               | 13       |
| Connecting the Gateway System to the Sun StorEdge 6130 Array                     | 21       |
| Making the Sun StorEdge 6130 Array SAN Storage Available                         | 25       |
| Cluster Power On Procedure   | 27       |
| Mounting File Systems  | 27       |
| Drive Letter Assignments to File Systems   | 27       |
| Adding Drives to the Sun StorEdge 5210 and 5310 NAS Appliance                    | 27       |
| Compliance Feature   | 28       |
| Online Help  | 28       |

|   |    |
|---|----|
| Upgrade to 4.10 Requires Resetting the Timezone               | 28 |
| Reintroduction of a LUN Requires a Reboot                     | 29 |
| CATIA V4/V5 Interoperability Support                          | 29 |
| Offline LUNs Cannot Be Deleted                                | 30 |
| Do Not Manually Mount /CVOL                                   | 30 |
| raidctl Command   | 30 |
| File Replication Using Clusters                               | 32 |
| Exporting a File Volume                                       | 32 |
| MIB Files   | 33 |
| NAS System Log Messages                                       | 33 |
| Identification of Specific Disks for Replacement              | 33 |
| Scheduling Multiple Checkpoints Per Volume                    | 34 |
| LUN Unmapping and Remapping Procedures for the Gateway System | 34 |
| How to Capture raidctl Command Output                         | 36 |
| Release Documentation   | 47 |
| Service Contact Information                                   | 47 |
| Third-Party License Agreement                                 | 48 |

# Sun StorEdge 5210 and 5310 NAS Appliance and Gateway System Release Notes

---

These release notes contain information for the Sun StorEdge™ 5210 and 5310 NAS Appliance and Gateway system software version 4.10 as well as subsequent qualifications to the release. The software is backward compatible with previous versions of Sun StorEdge 5210 and 5310 NAS Appliance software.

When installing the Sun StorEdge 5310 Cluster, use these release notes with the *Sun StorEdge 5310 NAS Appliance and Gateway System Getting Started Guide*, 819-3237-10.

These release notes contain the following sections:

- “System Requirements” on page 2
- “Software Updates” on page 3
- “New Features” on page 3
- “Resolved Issues” on page 5
- “Known Issues” on page 7
- “Addenda to the Documentation” on page 12
- “Release Documentation” on page 47
- “Service Contact Information” on page 47
- “Third-Party License Agreement” on page 48

---

**Important** – The Web Administrator supports only a single login at a time. A best practice would thus be to have only one person administering the system at a time to avoid command conflicts. In a cluster configuration, you must log in to each server separately to manage that server.

---

---

# System Requirements

The Sun StorEdge 5210 and 5310 NAS Appliance system ships with the Web Administrator software already installed. You do not need to install any software to manage the Sun StorEdge 5210 and 5310 NAS Appliance.

To access the Web Administrator management interface, you must have a network-attached computer running one of the following browsers. You must use a Java™ technology-enabled browser with Java Plug-In 1.3.1 (minimum version).

- Internet Explorer
- Mozilla™
- Netscape Navigator™

---

**Note** – To download the latest Java Plug-in software, go to <http://java.com>.

---

## ▼ To Determine NAS OS Software and Build Versions

Perform one of the following procedures.

- Access the Web Administrator navigation panel and select System Operations → Update Software.
- Type `version`, on the command-line interface (CLI), and, for example, build 18 will display:

```
4.10 M0 (build 18)
```

## ▼ To Determine Firmware Revision Levels

Use the `raidctl profile` command to determine and record the current firmware revision level of each RAID controller unit, expansion unit, controller NVSRAM, and drive.

See “How to Capture `raidctl` Command Output” on page 36 for details.

---

# Software Updates

Please upgrade your system by downloading the latest version of NAS software from <http://sunsolve.sun.com>. Select the Patchfinder link, and then enter the patch number that is appropriate for your system.

- 118216 Software for the Sun StorEdge 5210 Appliance
- 119351 Software for the Sun StorEdge 5310 Appliance

---

**Note** – If you are upgrading a Sun StorEdge 5210 NAS Appliance to software version 4.10 from a release prior to version 4.05, FCO 257 is required. Contact Sun Service to get FCO 257 applied prior to upgrading your software. Any Sun StorEdge 5210 NAS Appliance with software version 4.05 (or greater) does not need the FCO applied.

---

---

# New Features

The following new enhancements are provided with release 4.10:

- The Sun StorEdge 5310 NAS Gateway system provides Network File System (NFS) and Common Internet File System (CIFS) file services for the following systems:
  - Sun StorEdge 9970, 9980, 9985, and 9990 systems
  - Sun StorEdge 6920 system, version 2.0.5
  - Sun StorEdge 6130 array. See “Connecting the Gateway System to the Sun StorEdge 6130 Array” on page 21 for installation instructions.
- The Sun StorEdge 5310 NAS Gateway system is qualified with the following Fibre Channel (FC) switches:
  - Brocade SilkWorm 3250, 3850, 3900, 4100, 200E, 24000, and 48000
  - Sun StorEdge 2 Gb 8, 16, and 64 port
  - McData Intrepid 6064, 6164, and Sphereon 4500
  - Qlogic 5200 and 5602
- The Sun StorEdge 5310 NAS Appliance and Gateway system are qualified with the following FC tape libraries when connected to an unused FC port on the Sun StorEdge 5310 NAS server. Disks and tape libraries cannot be attached to the same FC port.

- Sun StorEdge L180/500/700
- Sun StorEdge L25/100
- Sun StorEdge LTO 3 drives
- Sun StorEdge LTO 2 drives
- Sun StorEdge SDLT 320 drives
- StorageTek 9940B and 9840C drives

If all FC ports are in use for disk storage, you can add a FC switch to the configuration to consolidate disk connectivity to two FC ports. This will free up the remaining FC ports for exclusive FC tape use.

Tape units can operate in both cluster and gateway configurations, but are available only to the NAS server to which they are connected. There is no clustering support for tape units. Tape units always function as if they are connected to a single NAS server.

- The Sun StorEdge 5310 NAS Appliance is qualified with mixed expansion units. The firmware revision levels listed in TABLE 1 are required for each component.

**TABLE 1** Required Array Firmware Levels

| Component                         | File Name              |
|-----------------------------------|------------------------|
| RAID controller                   | SNAP_288X_06120910.dlp |
| RAID controller NVSRAM            | N2882-612843-503.dlp   |
| Fibre Channel expansion unit (EU) | esm9631.s3r            |
| SATA expansion unit (EU)          | esm9722.dl             |

See “Upgrading Array Firmware (No Reboot Required)” on page 16 for information about how to upgrade controller units, expansion units, and drives to the latest firmware revision level.

Mixed Serial Advanced Technology Attachment (SATA) and Fibre Channel expansion unit (EU) configurations are now supported with the following stipulations.

- Full EUs must consist of all Fibre Channel drives or all SATA drives. Mixing of drive types within an EU is not supported.
- The controller tray can contain Fibre Channel drives even if the EUs contain SATA drives. The controller tray cannot contain SATA drives.
- A unique hot-spare must be available for both SATA and Fibre Channel in the same capacity as used in the array.
- LUNs cannot include both SATA and Fibre Channel drives.

- Expansion trays connected to RAID controllers must be at the same firmware level as the controllers. For example, if you add an expansion tray of SATA drives at firmware level 1.2 to a NAS server with RAID controllers at firmware level 1.0, you must upgrade the entire system to revision level 1.2.
- The Sun StorEdge 5310 NAS Appliance is qualified with 300 GB Fibre Channel (FC) drives. The minimum drive firmware level for the 300 GB FC drive is 055A. If you are adding these drives to an existing controller unit, firmware on the array controller will need to be updated. (See “Upgrading Array and Drive Firmware Revision Levels” on page 13.)
- The Sun StorEdge 5210 and 5310 NAS Appliance provides In-Band RAID Management (IBRM). With release 4.10, the management of LUNs and RAID configurations is now included in the user interface for the. Previously, LUN management was only available for Sun StorEdge 5210 NAS Appliance configurations. (IBRM is not supported for Gateway configurations.)
- The Sun StorEdge 5310 NAS Gateway system now supports RAID 0+1.
- The product includes a new documentation set consisting of the following:
  - *Sun StorEdge 5310 NAS Appliance and Gateway System Getting Started Guide* which provides initial installation and initial setup information.
  - *Sun StorEdge 5310 NAS Appliance and Gateway System Administration Guide* which describes how to use the Web Administrator software to set up and monitor the system. It also includes instructions on using the command-line interface (CLI).
- CATIA V4/V5 products (developed by Dassault Systemes) now interoperate with the Sun StorEdge 5210 and 5310 NAS Appliance and Gateway systems.  
See “CATIA V4/V5 Interoperability Support” on page 29 for information about character translations and how to enable CATIA V4/V5 interoperability support.

---

## Resolved Issues

The following issues have been resolved with this release.

- When a Sun StorEdge 6920 is used as storage for the Sun StorEdge 5310 Gateway system, LUN and volume information will now display properly in the Web Administrator.
- A backup and restore of a directory of hard links should now work correctly. Previously the filesystem became read-only in certain circumstances.
- After a LUN failover was initiated from one head to another in a cluster system occasionally a LUN would not failback correctly resulting in incorrect head ownership and I/O failure. All LUNs will now failback to ownership by the correct head.

- The system can now process detached LUNs. In the previous release, the system would enter a panic state when processing detached LUNs.
- The system now allows you to create multiple LUNs. In the previous release, the server crashed when attempting to create multiple LUNs.
- ISO8859 code pages with extended (8-bit) ASCII characters now display properly.
- It is now possible to correctly mount a `/vol* .chkpnt` volume at the root level. Mounting a checkpoint volume using the following command will no longer cause a `pwd` command malfunction.

```
mount -F nfs se5k:/vol01.chkpnt /z/vlcp
```

- The Simple Network Management Protocol (SNMP) attribute `system.sysDescr.0` is now set correctly.
- All checkpoints now list the Backup option.
- The Environmental Monitoring Unit (EMU) boards in the Sun StorEdge 5210 NAS Appliance expansion unit are now properly instrumented and monitored.
- The network-attached storage (NAS) head no longer sends false battery errors under any circumstances.
- The File Transfer Protocol (FTP) module in the NAS operating system now loads automatically at startup but remains disabled by default.
- The graphical user interface (GUI) now has no limit to the number of external expansion units it will display.
- The console now displays all file volumes, even if more than 50 were created.
- Create and Delete bonding (port aggregate) occasionally caused an unresponsive system; this has been fixed.
- Large Network Data Management Protocol (NDMP) backup will not fill up `/dvol` with NDMP job files.
- SNMP attribute `se5210RaidBBUStatus` is set to "normal."
- On a Common Storage Module (CSM) redundant array of independent disks (RAID) controller hardware failure, pulling out the controller with active I/O no longer causes volumes to go Read-Only.
- Occasional disk or Fibre Channel errors while running I/Os no longer cause some volumes to be marked Read-Only.
- A RAID volume will now automatically start rebuilding on an Expansion Unit Fibre (EU F (with a space between the U and F)) expansion unit during use of existing hot-spares.
- NDMP Direct Access Restore (DAR) recovery will work with Backup Type set to "tar."
- Web Administrator will indicate read-only volumes if there is a LUN failure.

- There are no longer inconsistencies between setting the time zone from the Telnet Menu/CLI and setting it from the Web Administrator.
- In-Band RAID management is now supported as of release 4.10, therefore the help topics are now valid.
- Old exports should no longer appear when there are no associated volumes.
- When a cluster is in failover mode, if a volume is created from the Alone head on a Logical Unit Number (LUN) that was originally owned by the Quiet head, applications accessing that volume should no longer get an EACCESS error during the cluster recovery process.
- If you add a new tray, you can assign ownership of an unowned LUN with the Web Administrator.
- When a mirrored volume is Promoted using the Web Administrator, a status message is now displayed on the GUI.
- The cluster should not lose time and get out of sync when under extreme load.

---

## Known Issues

The following issues are not resolved at this time.

- The user information in Windows Active Directory Servers (ADS) may be deleted during use of the NAS autohome feature.

**Workaround:** Do not use the predefined “Users” container to publish the autohome share. Alternatively, if a user does not access the autohome share from the directory, it is not necessary to specify an ADS container in the autohome setup.

It is recommended that administrators create a new organization unit (container) for all the published shares. If there are multiple Sun StorEdge NAS systems in the domain, use a separate container for each Sun StorEdge NAS system to prevent the share published by one system from being overwritten by another system.

- The alternate path is not available after a restore for a LUN whose primary path is set after a Fibre Channel cable pull.

**Workaround:** After physical changes to the back-end configuration, a user-initiated rescan is required. Using the Web Administrator, go to Volume Operations → Create File Volumes and click Scan for New Disks.

- Upgrading CRM firmware using In-Band RAID Management (IBRM) might cause all LUNs on the Sun StorEdge 6130 array to failover to a single RAID controller.

**Workaround:** Place the \*LUNS\* back on the \*primary\* path by using the Web Administrator.

- An NDMP recover has mismatch on timestamp for the intermediate directories  
An NDMP recover may restore the mid-level directories with an incorrect “creation” timestamp. However, the target directories and files will be recovered with the correct timestamp.
- If the Sun StorEdge 5210 or 5310 NAS Appliance is shut down in a method other than the Web Administrator, or if the Web Administrator loses contact with the Sun StorEdge 5310 NAS Appliance, the browser may stop working.

**Workaround:** Close all instances of the Web Administrator and web browsers. After the system reboots, reopen a web browser and relaunch the Java browser interface.

- The Notification Email URL field shows the hostname URL. You might not be able to connect to the Web Administrator by clicking this URL.

**Workaround:** If the Domain Naming System (DNS) does not resolve the hostname, use the IP address to connect to the Sun StorEdge 5210 or 5310 NAS Appliance. Ensure that the host name defined in the Sun StorEdge 5210 or 5310 NAS Appliance is registered in a name server (for example, DNS or Network Information System (NIS)).

- High Availability and Port aggregation bond IP address may not restore properly after you delete a bond.

**Workaround:** Select a different IP address for the bond.

- Poor RX/TX optical signal strength may result in degraded performance.

**Workaround:** If there are no other critical hardware errors and you see significant performance degradation, this degradation could be related to Fibre Channel link errors. Contact Sun Service for assistance. (See “Service Contact Information” on page 47.)

- When you choose Configure NFS → Setup Hosts → Add User, the window contents don’t refresh, and the system appears to stop working because of many entries in the NIS/NIS+ mappings.

Wait for the system to finish processing and repaint the screen. Do not reboot your system.

- The Apply button becomes unusable when you attempt to create a LUN with more than six SATA drives from the Manage Raid option of the Web Administrator.

**Workaround:** When reconfiguring SATA drives using the Web Administration tools, be sure to not go over the 2.0 Terabyte LUN maximum size limit of the RAID controller.

- The Web Administrator stops receiving input from the keyboard. The mouse input continues to work.

**Workaround:**

1. On UNIX systems, close your browser and end the `java_vm` process. On Windows systems, quit your browser, open the Windows Task Manager, and select the Process tab.
2. Ensure that all browser processes have ended.
3. Restart your browser to start a new Java virtual machine (JVM) process and resume normal operation.

This is an issue between certain JVMs and browsers.

- Attempts to log in to a system with an offline LUN using the Web Administrator results in an error of "Login rejected." Attempting to delete a volume from an offline LUN results in the server not responding.

**Workaround:** This can occur when an offline LUN caused by a double fault is followed by a deletion of a file system from that LUN. A reboot is required.

## Cluster-Specific Issues (Sun StorEdge 5310 Cluster Only)


The following cluster-specific issues are not resolved at this time.

- The Alone head could become stuck in the transition state while the Quiet head is in the Quiet state.

**Workaround:** Perform another recover from the Alone head to ensure that your clusters are in Normal mode before doing any upgrades.

- In a cluster system using In-Band RAID Management (IBRM), it is important that the HBA ports on head 2 link to the same RAID Controller as the ports on head 1 using the same sequence. The setup needs to be mirrored.

For example, if HBA port 2 on Head 1 is connected to Controller A, then HBA port 2 on Head 2 must be connected to Controller A on the same array controller. See FIGURE 1 for an example.



**FIGURE 1** Relationship of HBA Ports to RAID Controllers

- Manual movement of LUNs between heads results in a zero capacity reading. This occurs during initial cluster setup or when you add new trays.

**Workaround:** Run a manual disk scan from either the Web Administrator or the Telnet Menu/CLI and the head will refresh the LUN capacity.

- In a cluster configuration, if the Quiet head experienced system problems during recovery, some of its volumes may fail to mount on the Alone head.

**Workaround:** Using the Telnet Menu / CLI, type the following command:

```
mount -f /volume-name
```

- In a cluster configuration, before doing a recovery, check the partner head using the LCD to see if the head is in Quiet mode. Then do the recovery from the Web Administrator or Telnet Menu of the Alone head.

If physical access to the system is not available, you should Telnet to the cluster system. You will be logged into the Alone head. From there you can either check the log to ensure that the Quiet head has finished booting, or ping the Quiet head's heartbeat. By default the heartbeat IP is 10.10.10.1 for head 1 and 10.10.10.2 for head 2.

- In a cluster configuration, a head should only modify file permissions on file systems owned by that head and not those owned by the partner head.

- Attempting to log in to the Web Administrator fails with a long delay and the message “Login rejected.”  
**Workaround:** Close all the browser instances, then restart the Web Administrator. This appears to occur with Mozilla variants of web browsers and not Internet Explorer.
- A new LUN created from cluster heads displays with owner as “Unowned.”  
**Workaround:** Assign LUN ownership using the Web Administrator GUI or Telnet/CLI.

## File Replicator-Specific Issues

The following replicator-specific issues are not resolved at this time.

- During creation of a new mirror, if the target/mirror system does not have enough space and partitions, then the source/master system continuously retries until enough space and partitions are available.  
**Workaround:** You can break the mirror. Then recreate the mirror after enough space and partitions are available on the target system.
- If there is a system failure (such as a power failure) within 10 seconds of the start of a change role process, both systems may be set as the TARGET and there will be no MASTER, causing loss of the mirror.  
**Workaround:** Contact Sun Technical Support for help in re-establishing your mirror.
- If you do a Change Role operation while there is heavy I/O activity on the master volume, the master might time out, and you might lose CIFS access to the volume.  
**Workaround:** Do a manual remount of the file volume from the CLI. For example, if the volume name is `volx`, type the following:

```
nas-5310> umount /volx
nas-5310> mount /volx
```

- The RESYNC option is not available in the Web Administrator.  
**Workaround:** This option is available via the Telnet menu.
- During mirroring with heavy I/O activity, or during mirroring with cluster systems, you might see the following messages in the logs of the target/mirror server:

```
nmir: deseq_recv: The mirror log appears to be full
```

**Workaround:** These messages are for informational purposes and the mirrors will continue with the normal operation. These messages can be safely ignored.

## Gateway-Specific Issues (Sun StorEdge 5310 Gateway System Only)

The following gateway-specific issues are not resolved at this time.

- A Gateway system does not support heterogeneous systems attached to the head. Only one storage system per Sun StorEdge 5310 Gateway system configuration, single head or cluster, is supported. You may not attach multiple storage systems.
- In a Gateway-clustered system, each head must have two Fibre Channel connections to a SAN storage unit. One Fibre Channel connection is insufficient for proper functionality.
- After you remap a LUN from other SAN hosts to the NAS Gateway system, the LUN may appear to be inaccessible.

**Workaround:** Run the CLI `disk disk-name` command. If the owner of the LUN is listed as “noDPMGR,” then the disk has residual data.

Run the following CLI command to clear the data and make the LUN usable.

```
disk disk_name ,partition-number zap
```



---

**Caution** – The `zap` command reformats the LUN. The disk table will be deleted.

---

## Addenda to the Documentation

This section includes information that is additional to or overrides information in the documentation. It contains the following topics.

- “Upgrading Array and Drive Firmware Revision Levels” on page 13
- “Connecting the Gateway System to the Sun StorEdge 6130 Array” on page 21
- “Cluster Power On Procedure” on page 27
- “Mounting File Systems” on page 27
- “Drive Letter Assignments to File Systems” on page 27
- “Adding Drives to the Sun StorEdge 5210 and 5310 NAS Appliance” on page 27
- “Compliance Feature” on page 28
- “Online Help” on page 28

- “Upgrade to 4.10 Requires Resetting the Timezone” on page 28
- “Reintroduction of a LUN Requires a Reboot” on page 29
- “CATIA V4/V5 Interoperability Support” on page 29
- “Offline LUNs Cannot Be Deleted” on page 30
- “Do Not Manually Mount /CVOL” on page 30
- “raidctl Command” on page 30
- “File Replication Using Clusters” on page 32
- “Exporting a File Volume” on page 32
- “MIB Files” on page 33
- “NAS System Log Messages” on page 33
- “Identification of Specific Disks for Replacement” on page 33
- “Scheduling Multiple Checkpoints Per Volume” on page 34
- “LUN Unmapping and Remapping Procedures for the Gateway System” on page 34
- “How to Capture raidctl Command Output” on page 36

## Upgrading Array and Drive Firmware Revision Levels

This section explains how to determine current array and drive firmware revision levels and how to upgrade your firmware. It contains the following topics:

- “Determining If You Need to Upgrade the Firmware” on page 13
- “Upgrading Array and Drive Firmware (Reboot Required)” on page 13
- “Upgrading Array Firmware (No Reboot Required)” on page 16
- “Upgrading Drive Firmware (Reboot Required)” on page 20

### Determining If You Need to Upgrade the Firmware

Before you begin a firmware upgrade, decide if an upgrade is required by determining the current firmware revision level for each array component.

You can use the `raidctl profile` command to capture and record the current firmware revision level of each RAID controller unit, expansion unit, controller NVSRAM, and drive. See “How to Capture `raidctl` Command Output” on page 36 for more information.

### Upgrading Array and Drive Firmware (Reboot Required)

Use this procedure to upgrade RAID array and drive firmware. This procedure requires you to reboot the NAS server.

If you cannot reboot the NAS server and need to upgrade only array firmware, refer to “Upgrading Array Firmware (No Reboot Required)” on page 16.

The amount of time required to complete a firmware upgrade will vary depending on your configuration. For example, it takes approximately 50 minutes to upgrade and reboot a single NAS server with two RAID controllers, one FC expansion unit, and one SATA expansion unit. See TABLE 1 to determine how much time to allow for your configuration.

---

**Note** – Upgrading drive firmware always requires a reboot of the NAS server.

---

---

**Note** – All drives of each drive type will be upgraded including those that are already at the firmware level of the current firmware file.

---



---

**Caution** – Do not perform this procedure if a drive has failed and is in the rebuilding state. You can see this information in the system log or from the Web Administrator RAID page.

---

Before you begin this procedure, make sure that the NAS server software version 4.10 Build 18 (minimum) is installed. Do not attempt to upgrade array and drive firmware for a NAS server that has a previous OS version.

1. **Download the latest patch from [www.sunsolve.sun.com](http://www.sunsolve.sun.com) and unzip the file.**
2. **Review the patch readme file to determine which firmware revision levels are associated with the patch.**
3. **From a NAS client, enable ftp.**

Refer to the *Sun StorEdge 5310 NAS Appliance and Gateway System Administration Guide* for information about how to enable ftp using the Web Administrator GUI or CLI.

4. **Change to the directory to which you downloaded the patch.**
5. **Use ftp to connect to the NAS server, and log in as the admin user.**
6. **Enter bin for binary mode.**
7. **At the ftp prompt, create the following directories on /cvol by entering these commands:**

```
mkdir /cvol/firmware
mkdir /cvol/firmware/2882
mkdir /cvol/firmware/2882/ctlr
```

```

mkdir /cvol/firmware/2882/nvsram
mkdir /cvol/firmware/2882/jbod
mkdir /cvol/firmware/2882/drive

```

**8. Change to the directory you created for the firmware and copy the firmware file (see TABLE 4) using the `put` command.**

For example, to load firmware for the RAID controller enter:

```

cd /cvol/firmware/2882/ctlr
put SNAP_288X_06120910.dlp

```

**9. Continue to load each firmware file to the appropriate directory.**

TABLE 2 lists the directory and example firmware file for each component.

**TABLE 2** Component Firmware Directories and Files

| Component                        | Directory                  | Example File Name           |
|----------------------------------|----------------------------|-----------------------------|
| RAID controller                  | /cvol/firmware/2882/ctlr   | SNAP_288X_06120910.dlp      |
| RAID controller NVSRAM           | /cvol/firmware/2882/nvsram | N2882-612843-503.dlp        |
| Fibre Channel EU                 | /cvol/firmware/2882/jbod   | esm9631.s3r                 |
| SATAEU                           | /cvol/firmware/2882/jbod   | esm9722.dl                  |
| Drive types:                     |                            |                             |
| Seagate ST314680                 | /cvol/firmware/2882/drive  | D_ST314680FSUN146G_0407.dlp |
| Seagate 10K                      | /cvol/firmware/2882/drive  | D_ST314670FSUN146G_055A.dlp |
| Hitachi 400GB<br>HDS724040KLSA80 | /cvol/firmware/2882/drive  | D_HDS7240SBSUN400G_AC7A.dlp |
| Fujitsu MAT3300F 300GB           | /cvol/firmware/2882/drive  | D_MAT3300FSUN300G_1203.dlp  |
| Seagate 10K 300GB                | /cvol/firmware/2882/drive  | D_ST330000FSUN300G_055A.dlp |

**10. Log out of the FTP session.**

**11. Telnet to the NAS server, and log in to a user account with admin privileges.**

**12. Reboot the system. For a cluster configuration, reboot both servers.**

TABLE 3 provides the approximate time needed to upgrade the firmware for each component.

**TABLE 3** Firmware Upgrade Time

| Component                  | Time to Complete Upgrade          |
|----------------------------|-----------------------------------|
| RAID controller            | Reboot plus 15 minutes            |
| RAID controller<br>NVS RAM | Reboot plus 5 minutes             |
| FC or SATA EU              | Reboot plus 5 minutes             |
| Drives                     | Reboot plus 1.5 minutes per drive |

**13. Verify that the new firmware has been loaded by entering this command:**

```
raidctl get type=lsi target=profile ctrl=0
```

You can also check the system log for failures.

## Upgrading Array Firmware (No Reboot Required)

This procedure upgrades RAID array firmware without requiring a reboot of the NAS server.

Before you begin this procedure, keep the following in mind:

- NAS server software version 4.10 Build 18 (minimum) must be installed. Do not attempt to upgrade firmware to a NAS server that has a previous OS version.
- This procedure is best performed with limited I/O activity. The controller will quiesce I/O during this procedure.



---

**Caution** – Do not perform this procedure if a drive has failed and is in the rebuilding state. You can see this information in the system log.

---

1. **Download the latest patch from [www.sunsolve.sun.com](http://www.sunsolve.sun.com) and unzip the file.**
2. **Review the patch `readme` file to determine which firmware revision levels are associated with the patch.**
3. **Change to the directory to which you downloaded the patch.**
4. **From a NAS client, enable `ftp`.**

Refer to the *Sun StorEdge 5310 NAS Appliance and Gateway System Administration Guide* for information about how to enable `ftp` using the Web Administrator GUI or CLI.

5. Use `ftp` to connect to the NAS server, and log in to a user account with admin privileges.

6. Enter `bin` for binary mode.

7. At the `ftp` prompt, create the following directories on `/cvol` by entering:

```
mkdir /cvol/firmware
mkdir /cvol/firmware/2882
mkdir /cvol/firmware/2882/ctlr
mkdir /cvol/firmware/2882/nvsram
mkdir /cvol/firmware/2882/jbod
```

8. Change to the directory you created for the firmware and copy the firmware file (see TABLE 4) using the `put` command.

For example, to load firmware for the RAID controller enter:

```
cd /cvol/firmware/2882/ctlr
put SNAP_288X_06120910.dlp
```

9. Continue to load each firmware file to the appropriate directory.

TABLE 4 lists the directory and example firmware file for each component.

**TABLE 4** Component Firmware Directories and Files

| Component                  | Directory                               | Example File Name                   |
|----------------------------|---|-------------------------------------|
| RAID controller            | <code>/cvol/firmware/2882/ctlr</code>   | <code>SNAP_288X_06120910.dlp</code> |
| RAID controller<br>NVS RAM | <code>/cvol/firmware/2882/nvsram</code> | <code>N2882-612843-503.dlp</code>   |
| Fibre Channel EU           | <code>/cvol/firmware/2882/jbod</code>   | <code>esm9631.s3r</code>            |
| SATA EU                    | <code>/cvol/firmware/2882/jbod</code>   | <code>esm9722.dl</code>             |

10. Log out of the FTP session.

11. Use Telnet to connect to the NAS server, and log in to a user account with admin privileges.

12. Use the `raidctl` download command to load each file to the target directory.

For example, to load the controller firmware from the `ctlr` directory to controller 0 and 1, enter this command:

```
raidctl download type=lsi target=ctlr ctlr=0
```

This command downloads the firmware file to both controllers and removes the file from the directory.

---

**Note** – The `raidctl download` command deletes the firmware file after each invocation of the command. Therefore, you must re-copy the firmware file after upgrading each component (controller unit, controller NVSRAM, expansion unit, drives).

---

To download the firmware located in the `jbod` directory to expansion enclosure 0, enter this command:

```
raidctl download type=lsi target=jbod ctlr=0
```

### 13. Monitor the progress of each download from the Telnet session.

The approximate time needed to complete each upgrade is as follows:

---

| Component              | Minutes per component |
|------------------------|-----------------------|
| RAID controller EU     | 15 minutes            |
| RAID controller NVSRAM | 5 minutes             |
| FC or SATA EU          | 5 minutes             |

---

**Note** – After the upgrades complete, the `telnet` cursor can take up to 5 minutes to return. Wait during this time until the cursor is displayed.

---

**14. Before continuing to the next component, verify in the system log that the download is complete.**

The following example shows output from the system log:

```
Ctrl-
Firmware Download 90% complete
Firmware Download 95% complete
Firmware Download 100% complete
Waiting for controllers to become ACTIVE
Controller 0 - now ACTIVE
Controller 1 - now ACTIVE
Controllers are now active
nvsram-

raidctl download type=lsi target=nvsram ctrl=0
Flashing C0 NVSRAM: /cvol/nf2/./firmware/2882/nvsram/n2882-
61.dlp (48068)
Firmware Download 100% complete
Waiting for controllers to become ACTIVE
Controller 0 - now ACTIVE
Controller 1 - now ACTIVE
Controllers are now active
ESM-
>> raidctl download type=lsi target=jbod ctrl=0 tray=1

Flashing C0 JBOD 1 with
/cvol/nf1/./firmware/2882/jbod/esm9631.s3r (663604)
Firmware Download 20% complete
Firmware Download 30% complete
Firmware Download 50% complete
Firmware Download 60% complete
Firmware Download 90% complete
Firmware Download 100% complete
Waiting for controllers to become ACTIVE
Controller 0 - now ACTIVE
Controller 1 - now ACTIVE
Controllers are now active
```

**FIGURE 2** Sample System Log Output

```
Drive-
10/26/05 10:57:42 I Firmware Download 20% complete
10/26/05 10:57:46 I Firmware Download 30% complete
10/26/05 10:57:50 I Firmware Download 40% complete
10/26/05 10:57:54 I Firmware Download 50% complete
10/26/05 10:57:58 I Firmware Download 60% complete
10/26/05 10:58:03 I Firmware Download 70% complete
10/26/05 10:58:08 I Firmware Download 80% complete
10/26/05 10:58:13 I Firmware Download 90% complete
10/26/05 10:58:18 I Bytes Downloaded: 628224 (2454 256 chunks),
imageSize=62804
      8
10/26/05 10:59:01 I Flashed OK - drive in tray 2 slot 12
10/26/05 10:59:01 I Downloaded firmware version 0407 to 27 drives
```

## Upgrading Drive Firmware (Reboot Required)

Use this procedure to upgrade only drive firmware. This procedure requires you to reboot the NAS server.

---

**Note** – Upgrading drive firmware always requires a reboot of the NAS server.

---

---

**Note** – All drives of each drive type will be upgraded including those that are already at the firmware level of the current firmware file.

---

The amount of time required to complete a firmware upgrade will vary depending on the number of drives that are installed plus the time to reboot the NAS server. See TABLE 1 to determine how much time to allow for your configuration.



---

**Caution** – Do not perform this procedure if a drive has failed and is in the rebuilding state. You can see this information in the system log.

---

Before you begin a drive firmware upgrade make sure that the NAS server software 4.10 Build 18 (minimum) is installed. Do not attempt to upgrade firmware to a NAS server that has a previous OS version.

1. **Download the latest patch from [www.sunsolve.sun.com](http://www.sunsolve.sun.com) and unzip the file.**
2. **Review the patch readme file to determine which firmware revision levels are associated with the patch.**

3. Change to the directory to which you downloaded the patch.

4. From a NAS client, enable FTP.

Refer to the *Sun StorEdge 5310 NAS Appliance and Gateway System Administration Guide* for information about how to enable ftp using the Web Administrator GUI or CLI.

5. Use FTP to connect to the NAS server and log in as the admin user.

6. Enter bin for binary mode.

7. At the ftp prompt, create the following directory on /cvol by entering this command:

```
mkdir /cvol/firmware/2882/drive
```

8. Change to the directory you created for the drive firmware and copy the drive firmware files (see TABLE 2) using the put command.

For example, to load firmware for the Seagate ST314680 drive enter:

```
cd /cvol/firmware/2882/drive
put D_ST314680FSUN146G_0407.dlp
```

9. Log out of the FTP session.

10. Use Telnet to connect to the NAS server and log in as the admin user.

11. Reboot the system. For a cluster configuration, reboot both servers.

The approximate time to complete the upgrade is reboot time plus 1.5 minutes for each drive.

12. Verify that the new firmware has been loaded by entering this command:

```
raidctl get type=lsi target=profile ctrlr=0
```

You can also check the system log for failures.

## Connecting the Gateway System to the Sun StorEdge 6130 Array

This section provides instructions for connecting and configuring the Sun StorEdge 5310 NAS Gateway system to the Sun StorEdge 6130 array. The procedure assumes that you have already done the following:

- Installed and configured the gateway system as described in the *Sun StorEdge 5310 NAS Appliance and Gateway System Getting Started Guide*.

- Installed and configured the array as described in the *Sun StorEdge 6130 Array Getting Started Guide* (part number 819-0032-nn).

## Cabling the Gateway System to the Sun StorEdge 6130 Array

You can connect the Gateway system directly to the Sun StorEdge 6130 array or through a single or dual Fibre Channel switches. A minimum of one port must be available on the NAS server and the 6130 array.

- Refer to the *Sun StorEdge 5310 NAS Appliance and Gateway System Getting Started Guide* for information about the NAS server ports and general installation instructions.
- Refer to the *Sun StorEdge 6130 Array Getting Started Guide* for information about the array ports and general installation instructions.

## Required Software and Firmware

The Sun StorEdge 5310 NAS Gateway system requires software version 4.10 (minimum) for gateway support.

The Sun StorEdge 6130 array requires the following software and firmware to interoperate with the gateway system:

**TABLE 5** Required Sun StorEdge 6130 Array Software and Firmware

| Software                                    | Version (minimum) | Patch ID  |
|---|-------------------|-----------|
| Sun StorEdge 6130 array management software | 1.3               | 118164-06 |
| Controller CRM-F firmware                   | 06.12.09.10       | 117856-18 |
| Array firmware installer                    |                   | 118185-14 |

## Upgrading the Sun StorEdge 5310 NAS Gateway System

1. If your Gateway system does not have software version 4.10 (minimum), download the latest version from <http://sunsolve.sun.com>.
2. Install the update as described in the `install.txt` file provided with the patch.

## Upgrading the Sun StorEdge 6130 Array Management Software

If the Sun StorEdge 6130 array is currently at version 1.2, upgrade the management software to version 1.3 before installing the patches.

If the Sun StorEdge 6130 array is currently at version 1.3, install the patches as described in “Upgrading the Sun StorEdge 6130 Array Firmware” on page 23.

To upgrade the management software:

1. **From the Sun StorEdge 6130 array management interface.**
2. **Log in to the Sun Storage Automated Diagnostic Environment and clear all existing alarms.**
3. **Log in to the management host as `root`.**
4. **Download the latest Sun StorEdge 6130 host software package v1.3 for Solaris from `http://sunsolve.sun.com` to any working directory on the management host.**
5. **Unzip the distribution file and untar the file.**
6. **Enter the following command:**

```
./upgrade -n
```

The `-n` option specifies a non-interactive upgrade. After asking whether you want to upgrade software or firmware, the script will complete the upgrade without pausing for questions.

When the installation is complete, a confirmation is displayed followed by the date and time that the upgrade finished.

You can now install the patches as described in the next section.

## Upgrading the Sun StorEdge 6130 Array Firmware

The Sun StorEdge 6130 array management software requires version 1.3 firmware before you can install the required patches.

To upgrade the firmware for the Sun StorEdge 6130 array:

1. **Download the required patches (see TABLE 5) from `http://sunsolve.sun.com/`.**
2. **Stop all I/O to the disk drives.**
3. **Log in to the management host as `root`.**
4. **Change to the directory to which you downloaded the software.**

5. Install each patch by following the instructions in the patch `README` file.
6. Verify that the latest patches are installed:
  - a. Open a supported browser.
  - b. Enter the IP address of the management host using this format:  
`https://host_IP:6789`
  - c. Log in to the management software.
  - d. Click **Sun StorEdge 6130 Configuration Service**.  
The Array Summary page is displayed.
  - e. Verify that the **Firmware Version** column displays **06.12.09.10** (or greater).

## Verifying the Array

To verify that the array is seen by the Sun StorEdge 6130 host software, use automatic discovery or manual registration.

### ▼ To Automatically Verify the Array

If the array is on the same subnet as the management host, you can automatically verify the array.

1. Open a supported browser.
2. Enter the IP address of the management host using this format:  
`https://host-IP:6789`
3. Log in to the management software.
4. Click **Sun StorEdge 6130 Configuration Service**.  
The Array Summary page is displayed.
5. On the Array Summary page, click **Auto Discover** to display arrays that are on the same subnet as the management host.

---

**Note** – It takes approximately 2 minutes for the software to discover each array.

---

6. Verify that the array is listed on the Array Summary page.

## ▼ To Manually Register the Array

If the array is not on the same subnet as the management host, you must manually register the array.

1. **Open a supported browser.**
2. **Enter the IP address of the management host using this format:**  
`https://host-IP:6789`
3. **Log in to management software.**
4. **Click Sun StorEdge 6130 Configuration Service.**  
The Array Summary page is displayed.
5. **On the Array Summary page, click Register Array.**  
The Array Registration page is displayed.
6. **Enter the IP address of the controller and click OK.**
7. **Verify that the array is listed on the Array Summary page.**

## Making the Sun StorEdge 6130 Array SAN Storage Available

To make the Sun StorEdge 6130 SAN storage available to the NAS Gateway system, do the following:

1. Create an initiator on the Sun StorEdge 6130 array
2. Define a new volume on the Sun StorEdge 6130 array
3. Define a NAS volume on the NAS server

## ▼ To Create an Initiator

1. **Log in to the Sun StorEdge 6130 Configuration Service software, and click Physical Storage > Initiators.**  
The Initiator Summary page is displayed.
2. **Click New.**  
The New Initiator Summary page is displayed.
3. **Enter a name for the new initiator, using a maximum of 30 characters.**
4. **Select an existing world wide name (WWN), or enter a new one.**

5. **Select the host name for the new initiator.**
6. **Select the Sun StorEdge host type for the initiator.**
7. **Click OK.**

The Initiator Summary page displays the initiator name, host name, host type, and WWN of the new initiator.

## ▼ To Define a Sun StorEdge 6130 Volume

1. **In the Sun StorEdge 6130 Configuration Service interface, click Logical Storage > Volumes.**

The Volume Summary page is displayed.

2. **Click New.**

The New Volume wizard is displayed.

3. **Enter a name and capacity for the volume.**

4. **Select the virtual disk you want to use for this volume.**

5. **Map the volume to the Sun StorEdge 5310 NAS Gateway host.**

The new volume is displayed on the Volume Summary page.

## ▼ To Define a NAS 5310 Volume

1. **From a client of the NAS server, log in to the Web Administrator.**

2. **Create a NAS volume on the Sun StorEdge 6130 volume and format it:**

- a. **Open the File Volume Operations menu.**

- b. **Select Create File Volumes.**

- c. **Click Scan New Disks.**

The newly created 6130 LUN is displayed on the left side of the center pane.

- d. **Name the volume, enter the required parameters, and click Apply.**

See the *Sun StorEdge 5310 NAS Appliance and Gateway System Administration Guide* for information about the required parameters.

## Cluster Power On Procedure

The cluster power-on procedure on page 78 of the *Sun StorEdge 5310 NAS Appliance and Gateway System Getting Started Guide* instructs you to power on server H1 first. To determine the H1 server, look for the software serial number (ending in -H1) on the label that is affixed to the back panel of the NAS server. If the label is not located at the back of the server, check the sheet metal on left side of the NAS server.

## Mounting File Systems

After multiple continuous reboots, one or more file systems may become unmounted. To mount the file systems, issue the following command:

```
mount -f volume-name
```

## Drive Letter Assignments to File Systems

During file system creation, the NAS will automatically assign a drive letter to file systems accessible by way of SMB/CIFS. It is possible to run out of drive letters, after which you may see the following log message:

```
No drive letter available
```

This message is for informational purposes only. The file system will be created but, to assign it a drive letter, you must reassign a drive letter that is currently used by another file system.

## Adding Drives to the Sun StorEdge 5210 and 5310 NAS Appliance

The Sun StorEdge NAS Appliance supports hot-plugging of drives. However, to add or remove expansion units, you must shut down the system.

## Compliance Feature

The following information applies to the Sun StorEdge 5310 Appliance and Cluster configurations.

- The compliance feature of worming a file through Microsoft Windows software is turned off by default.

To turn the Windows trigger on, use the following CLI command:

```
fsctl compliance wte on
```

- When a compliance license expires or is removed, the system will maintain compliance rules, but no new compliance volumes can be created.

## Online Help

### Check Rate Field

The Set Up NIS panel is missing a description for the Check Rate field. The description of the Check Rate field is as follows:

Check Rate - Enter the frequency in minutes you want the NIS information to be refreshed. The default is five minutes.

### Locate Drive and Locate Drive Tray

The Locate Drive and Locate Drive Tray pages are missing from the online help. To determine these parameters, bring up the Web Administrator GUI navigation panel and select RAID → Manage RAID. The Manage RAID Panel is displayed. Then click the Locate Drive or Locate Drive Tray button. This causes the LCD indicator for the drive or drive tray to flash.

## Upgrade to 4.10 Requires Resetting the Timezone

When upgrading to 4.10, you will be asked to re-enter timezone information, even though it was previously entered. This is due to a changed implementation that offers additional timezone locations.

## Reintroduction of a LUN Requires a Reboot

A reboot is required when a LUN is deleted and then reintroduced to the NAS using a method other than In-Band RAID Management.

A server reboot is not required for the gateway system. You can unmap and remap the LUN as described in “LUN Unmapping and Remapping Procedures for the Gateway System” on page 34.

## CATIA V4/V5 Interoperability Support

CATIA V4 is a UNIX-only product, whereas CATIA V5 is available on both UNIX and Windows platforms. CATIA V4 may use certain characters in file names that are invalid in Windows. When CATIA customers migrate from V4 to V5, V4 files may become inaccessible in Windows if their file names contain invalid Windows characters. Therefore, a character translation option is provided for CATIA V4/V5 UNIX/Windows interoperability. The translation table is shown in TABLE 6:

**TABLE 6** CATIA Character Translation Table

| CATIA V4 UNIX Character                  | CATIA V5 Windows Character | CATIA V5 Character Description             |
|--|----------------------------|--|
| Curved open double quotation (not shown) | ¨                          | Dieresis                                   |
| *  | ¤                          | Currency sign                              |
| /  | ø                          | Latin small letter O with stroke           |
| :  | ÷                          | Division sign                              |
| <  | «                          | Left-pointing double angle quotation mark  |
| >  | »                          | Right-pointing double angle quotation mark |
| ?  | ¿                          | Inverted question mark                     |
| \  | ÿ                          | Latin small letter Y with dieresis         |
|  | Broken bar (not shown)     | Broken bar                                 |

CATIA V4/V5 interoperability support is disabled by default. You can enable the feature either manually through the CLI or automatically after a system boot.

## ▼ To Enable CATIA Using the CLI

Issue the following CLI command, `load catia`. When using this method, you must re-enable CATIA support after each system reboot.

## ▼ To Enable CATIA Automatically On Reboot

1. **Edit `/dvol/etc/inetload.ncf` to add the word `catia` on a separate line within the file.**
2. **Issue the following two CLI commands to restart the `inetload` service:**
  - `unload inetload`
  - `load inetload`
3. **If CATIA V4/V5 support was successfully enabled, an entry similar to the following is displayed in the system log:**

```
07/25/05 01:42:16 I catia: $Revision: 1.1.4.1
```

## Offline LUNs Cannot Be Deleted

LUNs or volumes that are offline cannot be deleted. A LUN must be brought online before it or its volumes can be deleted.

## Do Not Manually Mount `/CVOL`

The `/cvol` file system should not be manually shared or mounted. Do not make modifications to `/cvol` using any method other than the Web Administrator or Telnet/CLI.

---

**Note** – Sun Support Engineers are authorized to perform a manual mount.

---

## `raidctl` Command

The `raidctl` command enables you to manage the Sun StorEdge 5310 NAS Appliance RAID controllers from the CLI. To get help on the `raidctl` subcommands, enter the `raidctl help` command.

## Controlling LEDs

Use the `raidctl locate` command to control the LEDs in a tray.

To cause all LEDs in the tray to blink, enter:

```
raidctl locate type=lsi target=tray ctrl=0..n tray=0..n
```

To cause a specified drive's LED to blink, enter:

```
raidctl locate type=lsi target=drive ctrl=0..n tray=0..n slot=1..n
```

To stop blinking LEDs for a specified controller, enter:

```
raidctl locate type=lsi action=stop ctrl=0..n
```

## Getting Events and Configuration Information

Use the `raidctl get` command to get RAID controller events and configuration information.

To get all events for a specified controller, enter:

```
raidctl get type=lsi target=events ctrl=0..n
```

The log of all events will be written to `/cvol/log/2882ae.log` file. If the file already exists, you will be prompted to overwrite the file, specify a new file name, or cancel the operation.

To get critical events for a specified controller, enter:

```
raidctl get type=lsi target=events ctrl=0..n etype=critical
```

The log of critical events will be written to `/cvol/log/2882ce.log` file. If the file already exists, you will be prompted to overwrite the file, specify a new file name, or cancel the operation.

To get configuration information for a specified controller, enter:

```
raidctl get type=lsi target=profile ctrl=0..n
```

## Setting the Controller Time and Battery Age

Use the `raidctl set` command to set the time and battery age of a RAID controller.

To reset a specified controller's battery age, enter:

```
raidctl set type=lsi target=battery-age ctrl=0..n
```

To synchronize a controller's time with the server's time, enter:

```
raidctl set type=lsi target=ctrl_time-age ctrl=0..n
```

## Downloading Firmware

Use the `raidctl` download command to download firmware. Download the firmware to the following directories:

| Component                 | Directory                                |
|---------------------------|--|
| RAID controller           | <code>/cvol/firmware/2882/ctlr/</code>   |
| RAID controller<br>NVSRAM | <code>/cvol/firmware/2882/nvsram/</code> |
| FC or SATA EU             | <code>/cvol/firmware/2882/jbod/</code>   |
| Disk                      | <code>/cvol/firmware/2882/drive/</code>  |

See “Upgrading Array and Drive Firmware Revision Levels” on page 13 for procedures.

To download firmware to a specified controller, enter:

```
raidctl download type=lsi target=ctlr ctlr=0..n
```

To download firmware to a specified controller’s NVSRAM, enter:

```
raidctl download type=lsi target=nvsram ctlr=0..n
```

To download firmware to a specified EU, enter:

```
raidctl download type=lsi target=jbod ctlr=0..n tray=1..n
```

To download firmware to a specified drive, enter:

```
raidctl download type=lsi target=drive ctlr=0..n tray=0..n slot=1..n
```

## File Replication Using Clusters

Do not perform mirror operations such as Change Role when a cluster is in a degraded state. Please refer to the *Sun StorEdge 5310 NAS Appliance and Gateway System Administration Guide*, 819-3238-10, for information on best practices.

## Exporting a File Volume

You can export a file volume only to a set of hosts with root permission (like Sun Solaris or UNIX) by adding the hosts to the “trusted group” using the Set Up Hosts window.

Another way of doing this is to add the set of hosts to a host group and then export the required file volume against this group using the “with Map Root User set to Root User” option.

## MIB Files

The Management Information Base (MIB) files are installed with the image in the *boot-directory/www/data/mib* directory; for example, */cvol/nf1/www/data/mib*.

The MIB files can also be found in the release software download from <http://sunsolve.sun.com>.

## NAS System Log Messages

If your system log contains error messages stating “Unowned SFS2” volumes, call Technical Support for assistance.

## Identification of Specific Disks for Replacement

This section applies only to non-Gateway systems.

If you have a disk drive failure, use the log entry to help you identify the specific disk (you can interpret disk locations in both the system log and diagnostic reports the same way). The following is a log entry example.

```
Controller 0 enclosure 0 row 0 column 6
```

To interpret such log entries, keep the following points in mind:

- Ignore any channel and target numbers.
- Controller numbering starts at 0. For example, the controllers in the first array are 0 (slot A) and 1 (slot B), and the controllers in the second array are 2 and 3.
- Enclosure numbering starts at 0 and is relative to the array to which it belongs. For example, if the first array has 2 enclosures they are identified as enclosure 0 and 1.
- Row numbering is always 0 for the Sun StorEdge 5310 Cluster System.
- Column numbering starts at 0 and specifies the slot number in the enclosure.

Thus, you can interpret the example as indicating slot 7 of the first enclosure in the first array.

---

**Note** – There is no standard way to identify which array is the first one and which is the second one. Typically, the first HBA port is connected to the first array, the second HBA port is connected to the second array, and so on.

---

## Scheduling Multiple Checkpoints Per Volume

Scheduled checkpoints per volume are limited to 5, but multiple checkpoints may be specified per schedule. The following is an example:

|    | Enabled | Description  | Days<br>SMTWTFS | Hours AM<br>M1234567890E | Hours PM<br>M1234567890E | Keep<br>Days + Hours |
|----|---------|--------------|-----------------|--------------------------|--------------------------|----------------------|
| 1. | Y       | MTWTF5am5pm  | -*****-         | -----*-----              | -----*-----              | 1 0                  |
| 2. | Y       | SunWed1pm    | *--*---         | -----                    | -*-----                  | 0 12                 |
| 3. | Y       | MWFmidnight  | -*-*-*          | *-----                   | -----                    | 0 3                  |
| 4. | Y       | Weekend      | *-----*         | *-----*                  | *-----*                  | 0 6                  |
| 5. | Y       | FriEvery2hrs | -----*          | *-*-*-*-*                | *-*-*-*-*                | 0 2                  |

## LUN Unmapping and Remapping Procedures for the Gateway System

This procedure explains how to unmap a SAN storage LUN associated with the StorEdge 5310 NAS Gateway system. It also describes how to remap a LUN if you need to access the data in the future.

A summary of the unmapping and remapping procedure is as follows:

1. Unmapping a LUN
  - a. Unmount the volumes that reside on the LUN you want to unmap.
  - b. Unmap the LUN using the SAN management host software.
  - c. Rescan the Gateway system LUNs.
2. Remapping a LUN
  - a. Remap the LUN using the SAN management host software.
  - b. Rescan the Gateway system LUNs.

- c. Remount the volumes you want to access.

The following procedures use the Sun StorEdge 6130 array as an example.

## ▼ To Unmap a LUN

1. Unmount the volume at the Gateway system:
  - a. Use Telnet to connect to the NAS Gateway system.
  - b. At the first prompt, type `admin` to start the CLI.
  - c. Type `mount` to list the volumes that are mounted on the LUN to be unmapped. The “Origin” column displays the name of the raw devices that contains the volumes. Note the names of the volumes (listed in the leftmost column) you want to unmount.
  - d. Unmount all volumes that reside on the LUN to be unmapped using the `umount` command. Type `mount` and verify that none of the volumes that belong to the LUN are mounted.
2. From the Sun StorEdge 6130 management host, unmap the LUN from the backend array.
  - a. Open a browser to `https://<hostname>:6789` and log in to the management software.
  - b. Click Sun StorEdge 6130 Configuration Service.
  - c. Click the array whose LUN you want to unmap.
  - d. Click the name of the LUN you want to unmap.
  - e. Click the Unmap button.
  - f. Click OK on the pop-up window to confirm that you want to delete the LUN.
3. Rescan at the Gateway system.
  - a. Identify the LUN you want to unmap.
  - b. Use Telnet to connect to the NAS Gateway system.
  - c. At the first prompt, type `menu` to start the character-based menu interface.
  - d. Enter the letter `d` to display the Disks and Volumes menu.
  - e. From the Disks and Volumes menu, enter `9` to scan for new disks (or LUNs). Wait for the message “Scanning for new disks, please wait...” to clear.

## ▼ To Remap a LUN

1. From the Sun StorEdge 6130 management host, remap the LUN at the backend array.
  - a. Open a browser to `https://<hostname>:6789` and log in to the management software.
  - b. Click Sun StorEdge 6130 Configuration Service.
  - c. Click the array whose LUN you want to remap.
  - d. Check the box next to the name of the LUN you want to remap.
  - e. Press the Map button.

The Map Volumes window is displayed.
  - f. Check the host to which you want to map the LUN.
2. Rescan the LUNs at the Gateway system:
  - a. Use Telnet to connect to the Gateway system.
  - b. At the first prompt, type `menu` to start the character-based menu interface.
  - c. Enter the letter `d` to display the Disks and Volumes menu.
  - d. From the Disks and Volumes menu, enter `9` to scan for new disks (or LUNs).

Wait for the message "Scanning for new disks, please wait..." to clear.
3. Remount the volumes at the Gateway system.
  - a. Use Telnet to connect to the Gateway system.
  - b. At the first prompt, type `admin` to start the CLI.
  - c. Mount all volumes that reside on the LUN that was remapped.
  - d. Type `mount` to verify that all of the volumes are remapped.

## How to Capture `raidctl` Command Output

You can use the `raidctl profile` command to determine the current firmware revision level of each RAID controller unit, expansion unit, controller NVSRAM, and drive. The following procedures are provided:

- "To Capture `raidctl` Command Output From a Solaris Client" on page 37
- "To Capture `raidctl` Output From a Windows Client" on page 46

## ▼ To Capture raidctl Command Output From a Solaris Client

1. From a Solaris client, type the `script` command and a file name. For example,  
`> script raidctl`
2. Use Telnet to connect to the NAS server.
3. Type the following `raidctl` command to collect the output.  
`raidctl get type=lsi target=profile ctrl=0`
4. Type `exit` to close the Telnet session.
5. Type `exit` again to close the file named `raidctl`.

The following example shows command output with firmware levels highlighted in bold:

```
telnet 10.8.1xx.x2
Trying 10.8.1xx.x2...
Connected to 10.8.1xx.x2.
Escape character is '^]'.
connect to (? for list) ? [menu] admin
password for admin access ? *****
5310 > raidctl get type=lsi target=profile ctrl=0

SUMMARY-----
Number of controllers: 2
Number of volume groups: 4
Total number of volumes (includes an access volume): 5 of 1024 used
    Number of standard volumes: 4
    Number of access volumes: 1
Number of drives: 28
Supported drive types: Fibre (28)
Total hot spare drives: 2
    Standby: 2
    In use: 0
Access volume: LUN 31
Default host type: Sun_SE5xxx (Host type index 0)
Current configuration
    Firmware version: PkgInfo 06.12.09.10
    NVSRAM version: N2882-612843-503
Pending configuration
```

CONTROLLERS -----

Number of controllers: 2

Controller in Tray 0, Slot B

Status: Online

Current Configuration

**Firmware version: 06.12.09.10**

**Appware version: 06.12.09.10**

**Bootware version: 06.12.09.10**

**NVSRAM version: N2882-612843-503**

Pending Configuration

Firmware version: None

Appware version: None

Bootware version: None

NVSRAM version: None

Transferred on: None

Board ID: 2882

Product ID: CSM100\_R\_FC

Product revision: 0612

Serial number: 1T44155753

Date of manufacture: Sat Oct 16 00:00:00 2004

Cache/processor size (MB): 896/128

Date/Time: Thu Nov 2 19:15:49 2006

Associated Volumes (\* = Preferred Owner):

lun4\* (LUN 3)

Ethernet port: 1

Mac address: 00.A0.B8.16.C7.A7

Host name: gei

Network configuration: Static

IP address: 192.168.128.106

Subnet mask: 255.255.255.0

Gateway: 192.168.128.105

Remote login: Enabled

Drive interface: Fibre

Channel: 2

Current ID: 124/0x7C

Maximum data rate: 200 MB/s

Current data rate: 200 MB/s

Data rate control: Fixed

Link status: Up

Topology: Arbitrated Loop - Private

World-wide port name: 20:02:00:A0:B8:16:C7:A7

World-wide node name: 20:00:00:A0:B8:16:C7:A7

Part type: HPFC-5400 revision 6

```
Drive interface: Fibre
  Channel: 2
  Current ID: 124/0x7C
  Maximum data rate: 200 MB/s
  Current data rate: 200 MB/s
Data rate control: Fixed
  Link status: Up
  Topology: Arbitrated Loop - Private
  World-wide port name: 20:02:00:A0:B8:16:C7:A7
  World-wide node name: 20:00:00:A0:B8:16:C7:A7
  Part type: HPFC-5400      revision 6
Host interface: Fibre
  Channel: 2
  Current ID: 255/0x3
  Maximum data rate: 200 MB/s
  Current data rate: 200 MB/s
  Data rate control: Auto
  Link status: Down
  Topology: Unknown
  World-wide port name: 20:07:00:A0:B8:16:C6:FB
  World-wide node name: 20:06:00:A0:B8:16:C6:F9
  Part type: HPFC-5400      revision 6
Host interface: Fibre
  Channel: 2
  Current ID: 255/0x3
  Maximum data rate: 200 MB/s
  Current data rate: 200 MB/s
  Data rate control: Auto
  Link status: Down
  Topology: Unknown
  World-wide port name: 20:07:00:A0:B8:16:C6:FB
  World-wide node name: 20:06:00:A0:B8:16:C6:F9
  Part type: HPFC-5400      revision 6

Controller in Tray 0, Slot A
  Status: Online
  Current Configuration
    Firmware version: 06.12.09.10
    Appware version: 06.12.09.10
    Bootware version: 06.12.09.10
    NVSRAM version: N2882-612843-503
  Pending Configuration
    Firmware version: None
    Appware version: None
    Bootware version: None
    NVSRAM version: None
    Transferred on: None
```

```
Board ID: 2882
Product ID: CSM100_R_FC
Product revision: 0612
Serial number: 1T44155741
Date of manufacture: Sun Oct 10 00:00:00 2004
Cache/processor size (MB): 896/128
Date/Time: Thu Nov  2 19:15:45 2006
Associated Volumes (* = Perferred Owner):
lun1* (LUN 0), lun2* (LUN 1), lun3* (LUN 2)
Ethernet port: 1
  Mac address: 00.A0.B8.16.C6.F9
  Host name: gei
  Network configuration: Static
  IP address: 192.168.128.105
  Subnet mask: 255.255.255.0
  Gateway: 192.168.128.105
  Remote login: Enabled
Drive interface: Fibre
  Channel: 1
  Current ID: 125/0x7D
  Maximum data rate: 200 MB/s
  Current data rate: 200 MB/s
  Data rate control: Fixed
  Link status: Up
  Topology: Arbitrated Loop - Private
  World-wide port name: 20:01:00:A0:B8:16:C6:F9
  World-wide node name: 20:00:00:A0:B8:16:C6:F9
  Part type: HPFC-5400      revision 6
Drive interface: Fibre
  Channel: 1
  Current ID: 125/0x7D
  Maximum data rate: 200 MB/s
  Current data rate: 200 MB/s
  Data rate control: Fixed
  Link status: Up
  Topology: Arbitrated Loop - Private
  World-wide port name: 20:01:00:A0:B8:16:C6:F9
  World-wide node name: 20:00:00:A0:B8:16:C6:F9
  Part type: HPFC-5400      revision 6
Host interface: Fibre
  Channel: 1
  Current ID: 255/0x0
  Maximum data rate: 200 MB/s
  Current data rate: 200 MB/s
  Data rate control: Auto
```

```
Link status: Down
Topology: Unknown
World-wide port name: 20:06:00:A0:B8:16:C6:FA
World-wide node name: 20:06:00:A0:B8:16:C6:F9
Part type: HPFC-5400      revision 6
Host interface: Fibre
Channel: 1
Current ID: 255/0x0
Maximum data rate: 200 MB/s
Current data rate: 200 MB/s
Data rate control: Auto
Link status: Down
Topology: Unknown
World-wide port name: 20:06:00:A0:B8:16:C6:FA
World-wide node name: 20:06:00:A0:B8:16:C6:F9
Part type: HPFC-5400      revision 6
```

VOLUME GROUPS-----

```
Number of volume groups: 4
Volume group 1 (RAID 5)
Status: Online
Tray loss protection: No
Associated volumes and free capacities:
    lun1 (681 GB)
Associated drives (in piece order):
Drive at Tray 0, Slot 7
Drive at Tray 0, Slot 6
Drive at Tray 0, Slot 5
Drive at Tray 0, Slot 4
Drive at Tray 0, Slot 3
Drive at Tray 0, Slot 8
Volume group 2 (RAID 5)
Status: Online
Tray loss protection: No
Associated volumes and free capacities:
    lun2 (681 GB)
Associated drives (in piece order):
Drive at Tray 0, Slot 14
Drive at Tray 0, Slot 13
Drive at Tray 0, Slot 12
Drive at Tray 0, Slot 11
Drive at Tray 0, Slot 10
Drive at Tray 0, Slot 9
```

Volume group 3 (RAID 5)  
 Status: Online  
 Tray loss protection: No  
 Associated volumes and free capacities:  
   lun3 (817 GB)  
 Associated drives (in piece order):  
 Drive at Tray 11, Slot 5  
 Drive at Tray 11, Slot 4  
 Drive at Tray 11, Slot 3  
 Drive at Tray 11, Slot 2  
 Drive at Tray 11, Slot 1  
 Drive at Tray 11, Slot 7  
 Drive at Tray 11, Slot 6

Volume group 4 (RAID 5)  
 Status: Online  
 Tray loss protection: No  
 Associated volumes and free capacities:  
   lun4 (817 GB)  
 Associated drives (in piece order):  
 Drive at Tray 11, Slot 13  
 Drive at Tray 11, Slot 12  
 Drive at Tray 11, Slot 11  
 Drive at Tray 11, Slot 10  
 Drive at Tray 11, Slot 9  
 Drive at Tray 11, Slot 8  
 Drive at Tray 11, Slot 14

STANDARD VOLUMES-----

SUMMARY

Number of standard volumes: 4

| NAME | STATUS  | CAPACITY | RAID | LEVEL | VOLUME | GROUP |
|------|---------|----------|------|-------|--------|-------|
| lun1 | Optimal | 681      | GB   | 5     |        | 1     |
| lun2 | Optimal | 681      | GB   | 5     |        | 2     |
| lun3 | Optimal | 817      | GB   | 5     |        | 3     |
| lun4 | Optimal | 817      | GB   | 5     |        | 4     |

DETAILS

Volume name: lun1  
Volume ID: 60:0A:0B:80:00:16:C6:F9:00:00:23:B4:43:4B:53:3A  
Subsystem ID (SSID): 0  
Status: Optimal  
Action: 1  
Tray loss protection: No  
Preferred owner: Controller in slot A  
Current owner: Controller in slot B  
Capacity: 681 GB  
RAID level: 5  
Segment size: 64 KB  
Associated volume group: 1  
Read cache: Enabled  
Write cache: Enabled  
Flush write cache after (in seconds): 8  
Cache read ahead multiplier: 1  
Enable background media scan: Enabled  
Media scan with redundancy check: Disabled

DRIVES-----

SUMMARY

Number of drives: 28  
Supported drive types: Fiber (28)

BASIC:

| CURRENT    | PRODUCT        | FIRMWARE      |               |                         |             |  |
|------------|----------------|---------------|---------------|-------------------------|-------------|--|
| TRAY,SLOT  | STATUS         | CAPACITY      | DATA RATE     | ID                      | REV         |  |
| <b>0,1</b> | <b>Optimal</b> | <b>136 GB</b> | <b>2 Gbps</b> | <b>ST314680FSUN146G</b> | <b>0307</b> |  |
| 0,7        | Optimal        | 136 GB        | 2 Gbps        | ST314680FSUN146G        | 0307        |  |
| 0,6        | Optimal        | 136 GB        | 2 Gbps        | ST314680FSUN146G        | 0307        |  |
| 0,5        | Optimal        | 136 GB        | 2 Gbps        | ST314680FSUN146G        | 0307        |  |
| 0,4        | Optimal        | 136 GB        | 2 Gbps        | ST314680FSUN146G        | 0307        |  |
| 0,3        | Optimal        | 136 GB        | 2 Gbps        | ST314680FSUN146G        | 0307        |  |
| 0,2        | Optimal        | 136 GB        | 2 Gbps        | ST314680FSUN146G        | 0307        |  |
| 0,14       | Optimal        | 136 GB        | 2 Gbps        | ST314680FSUN146G        | 0307        |  |
| 0,13       | Optimal        | 136 GB        | 2 Gbps        | ST314680FSUN146G        | 0307        |  |
| 0,12       | Optimal        | 136 GB        | 2 Gbps        | ST314680FSUN146G        | 0307        |  |
| 0,11       | Optimal        | 136 GB        | 2 Gbps        | ST314680FSUN146G        | 0307        |  |
| 0,10       | Optimal        | 136 GB        | 2 Gbps        | ST314680FSUN146G        | 0307        |  |
| 0,9        | Optimal        | 136 GB        | 2 Gbps        | ST314680FSUN146G        | 0307        |  |
| 0,8        | Optimal        | 136 GB        | 2 Gbps        | ST314680FSUN146G        | 0307        |  |

|       |         |        |        |                  |      |
|-------|---------|--------|--------|------------------|------|
| 11,5  | Optimal | 136 GB | 2 Gbps | ST314680FSUN146G | 0307 |
| 11,4  | Optimal | 136 GB | 2 Gbps | ST314680FSUN146G | 0307 |
| 11,3  | Optimal | 136 GB | 2 Gbps | ST314680FSUN146G | 0307 |
| 11,2  | Optimal | 136 GB | 2 Gbps | ST314680FSUN146G | 0307 |
| 11,1  | Optimal | 136 GB | 2 Gbps | ST314680FSUN146G | 0307 |
| 11,13 | Optimal | 136 GB | 2 Gbps | ST314680FSUN146G | 0307 |
| 11,12 | Optimal | 136 GB | 2 Gbps | ST314680FSUN146G | 0307 |
| 11,11 | Optimal | 136 GB | 2 Gbps | ST314680FSUN146G | 0307 |
| 11,10 | Optimal | 136 GB | 2 Gbps | ST314680FSUN146G | 0307 |
| 11,9  | Optimal | 136 GB | 2 Gbps | ST314680FSUN146G | 0307 |
| 11,8  | Optimal | 136 GB | 2 Gbps | ST314680FSUN146G | 0307 |
| 11,7  | Optimal | 136 GB | 2 Gbps | ST314680FSUN146G | 0307 |
| 11,6  | Optimal | 136 GB | 2 Gbps | ST314680FSUN146G | 0307 |
| 11,14 | Optimal | 136 GB | 2 Gbps | ST314680FSUN146G | 0307 |

HOT SPARE COVERAGE:

The following volume groups are not protected:

Total hot spare drives: 2

Standby: 2

In use: 0

DETAILS:

Drive at Tray 0, Slot 1 (HotSpare)

Available: 0

Drive path redundancy: OK

Status: Optimal

Raw capacity: 136 GB

Usable capacity: 136 GB

Product ID: ST314680FSUN146G

Firmware version: 0307

Serial number: 3HY90HWJ00007510RKKV

Vendor: SEAGATE

Date of manufacture: Sat Sep 18 00:00:00 2004

World-wide name: 20:00:00:11:C6:0D:BA:3E

Drive type: Fiber

Speed: 10033 RPM

Associated volume group: None

Available: No

Vendor: SEAGATE  
Date of manufacture: Sat Sep 18 00:00:00 2004  
World-wide name: 20:00:00:11:C6:0D:CA:12  
Drive type: Fiber  
Speed: 10033 RPM  
Associated volume group: 3  
Available: No

Drive at Tray 11, Slot 1  
Drive path redundancy: OK  
Status: Optimal  
Raw capacity: 136 GB  
Usable capacity: 136 GB  
Product ID: ST314680FSUN146G  
Firmware version: 0307  
Serial number: 3HY90JEW00007511BDPL  
Vendor: SEAGATE  
Date of manufacture: Sat Sep 18 00:00:00 2004  
World-wide name: 20:00:00:11:C6:0D:C8:8B  
Drive type: Fiber  
Speed: 10033 RPM  
Associated volume group: 3  
Available: No

Drive Tray 1 Overall Component Information

Tray technology: Fibre Channel  
Minihub datarate mismatch: 0  
Part number: PN 54062390150  
Serial number: SN 0447AWF011  
Vendor: VN SUN  
Date of manufacture: Mon Nov 1 00:00:00 2004  
Tray path redundancy: OK  
Tray ID: 11

Tray ID Conflict: 0

Tray ID Mismatch: 0  
Tray ESM Version Mismatch: 0  
Fan canister: Optimal  
Fan canister: Optimal  
Power supply canister  
Status: Optimal  
Part number: PN 30017080150  
Serial number: SN A6847502330F  
Vendor: VN SUN  
Date of manufacture: Sun Aug 1 00:00:00 2004

```
Power supply canister
  Status: Optimal
  Part number: PN 30017080150
  Serial number: SN A6847502330F
  Vendor: VN SUN
  Date of manufacture: Sun Aug  1 00:00:00 2004
Power supply canister
  Status: Optimal
  Part number: PN 30017080150
  Serial number: SN A68475023N0F
  Vendor: VN SUN
  Date of manufacture: Sun Aug  1 00:00:00 2004
Temperature: Optimal
Temperature: Optimal
Esm card
  Status: Optimal
  Firmware version: 9631
  Maximum data rate: 2 Gbps
  Current data rate: 2 Gbps
  Location: A (left canister)
  Working channel: -1
  Product ID: CSM100_E_FC_S
  Part number: PN 37532180150
  Serial number: SN 1T44462572
  Vendor: SUN
  FRU type: FT SBOD_CEM
  Date of manufacture: Fri Oct  1 00:00:00 2004
Esm card
  Status: Optimal
  Firmware version: 9631
  Maximum data rate: 2 Gbps
  Current data rate: 2 Gbps
  Location: B (right canister)
  Working channel: -1
```

## ▼ To Capture raidctl Output From a Windows Client

1. Click **Start > Run** and type `cmd`. Click **OK**.
2. **Right click at the top of the window** and choose **Properties**.  
The Properties dialog is displayed.
3. **Change the Screen Buffer size (height) to 3000**.
4. **Click the Options tab and uncheck Insert Mode**.

5. Telnet to the NAS server and type the following `raidctl` command to collect the output.  

```
raidctl get type=lsi target=profile ctrl=0
```
6. Copy the text to a file using any text editor. For example:
  - a. Select the output text and enter Control-C to copy the data.
  - b. Open Wordpad by clicking Start > Programs > Accessories > Wordpad.
  - c. Click in the window and press Control-V to paste the text.
  - d. Save the file.
7. Open the file and search for the current firmware version for each component.

---

## Release Documentation

The following documentation is posted on the documentation Web site at:

[http://www.sun.com/hwdocs/Network\\_Storage\\_Solutions/nas](http://www.sun.com/hwdocs/Network_Storage_Solutions/nas).

---

| <b>Title</b>  | <b>Part Number</b> |
|---|--------------------|
| <i>Sun StorEdge 5310 NAS Gateway System Poster</i>  | 819-3240-10        |
| <i>Sun StorEdge 5310 NAS Appliance and Gateway System Getting Started Guide</i>                               | 819-3237-10        |
| <i>Sun StorEdge 5310 NAS Appliance and Gateway System Administration Guide</i>                                | 819-3238-10        |
| <i>Sun StorEdge 5310 NAS Appliance Safety and Compliance Guide</i>  | 819-0881-10        |
| <i>Sun StorEdge 5300 RAID Expansion Unit and Sun StorEdge 5300 Expansion Unit Safety and Compliance Guide</i> | 819-0882-10        |

---

---

## Service Contact Information

If you need help installing or using this product, call 1-800-USA-4SUN, or go to:

<http://www.sun.com/service/contacting/index.html>

---

# Third-Party License Agreement

## Introduction

1 The software provided as part of the Sun StorEdge 5210, 5310, 5310C NAS Appliance or Sun StorEdge 5310 NAS Gateway system may contain code provided by the following organizations or individuals under the described licenses.

2 The University of California Berkley Software Distribution License  
Copyright (c) 1991 The Regents of the University of California.  
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: 1.Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. 2.Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. 3.All advertising materials mentioning features or use of this software must display the following acknowledgement: This product includes software developed by the University of California, Berkeley and its contributors. 4.Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission. THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

3 NetBSD License  
Copyright (c) 1998 The NetBSD Foundation, Inc.  
All rights reserved.

This code is derived from software contributed to The NetBSD Foundation by Lennart Augustsson (lennart@augustsson.net) at Carlstedt Research & Technology.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: 1.Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. 2.Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. 3.All advertising materials mentioning features or use of this software must display the following acknowledgement: This product includes software developed by the NetBSD Foundation, Inc. and its contributors. 4.Neither the name of The NetBSD Foundation nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission. THIS SOFTWARE IS PROVIDED BY THE NETBSD FOUNDATION, INC. AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE FOUNDATION OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

4 The Massachusetts Institute of Technology License  
Copyright 1990 by the Massachusetts Institute of Technology.  
All Rights Reserved.

Export of this software from the United States of America may require a specific license from the United States Government. It is the responsibility of any person or organization contemplating export to obtain such a license before exporting. WITHIN THAT CONSTRAINT, permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of M.I.T. not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. Furthermore if you modify this software you must label your software as modified software and not distribute it in such a fashion that it might be confused with the original M.I.T. software. M.I.T. makes no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

5 The OpenVision Technologies Inc License  
Copyright 1993 by OpenVision Technologies, Inc.

Permission to use, copy, modify, distribute, and sell this software and its documentation for any purpose is hereby granted without fee, provided that the above copyright notice appears in all copies and that both that copyright notice and

this permission notice appear in supporting documentation, and that the name of OpenVision not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. OpenVision makes no representations about the suitability of this software for any purpose. It is provided "as is" without express or implied warranty.

OPENVISION DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL OPENVISION BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

6 The University of Michigan License  
Copyright (c) 1990 Regents of the University of Michigan.  
All rights reserved.

Redistribution and use in source and binary forms are permitted provided that this notice is preserved and that due credit is given to the University of Michigan at Ann Arbor. The name of the University may not be used to endorse or promote products derived from this software without specific prior written permission. This software is provided "as is" without express or implied warranty.

7 The Internet Software Consortium License  
Copyright (c) 1997 The Internet Software Consortium.  
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: 1.Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. 2.Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. 3.Neither the name of The Internet Software Consortium nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission. THIS SOFTWARE IS PROVIDED BY THE INTERNET SOFTWARE CONSORTIUM AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE INTERNET SOFTWARE CONSORTIUM OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,

WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

#### 8 Carnegie Mellon University License

The Carnegie Mellon University license appears in an SNMP header file.

Copyright 1988, 1989 by Carnegie Mellon University

All Rights Reserved

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation, and that the name of CMU not be used in advertising or publicity pertaining to distribution of the software without specific, written prior permission. CMU DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE, INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS, IN NO EVENT SHALL CMU BE LIABLE FOR ANY SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

#### 9 Troll FTP License

Copyright 1995-2000 Trolltech AS. Copyright 2001 Arnt Gulbrandsen.

Use, modification and distribution is allowed without limitation, warranty, or liability of any kind.

#### 10 RSA Data Security, Inc. Message Digest License

Copyright (C) 1991-2, RSA Data Security, Inc. Created 1991.

All rights reserved.

License to copy and use this software is granted provided that it is identified as the "RSA Data Security, Inc. MD4 Message-Digest Algorithm" in all material mentioning or referencing this software or this function. License is also granted to make and use derivative works provided that such works are identified as "derived from the RSA Data Security, Inc. MD4 Message-Digest Algorithm" in all material mentioning or referencing the derived work. RSA Data Security, Inc. makes no representations concerning either the merchantability of this software or the suitability of this software for any particular purpose. It is provided "as is" without express or implied warranty of any kind. These notices must be retained in any copies of any part of this documentation and/or software.

#### 11 MD5 License "THE BEER-WARE LICENSE" (Revision 42):

<phk@login.dknet.dk> wrote this file. As long as you retain this notice you can do whatever you want with this stuff. If we meet some day, and you think this stuff is worth it, you can buy me a beer in return. Poul-Henning Kamp

## 12 NIS License

Copyright (c) 1996, 1997 Bill Paul <wpaul@ctr.columbia.edu>.

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: 1.Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. 2.Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. 3.All advertising materials mentioning features or use of this software must display the following acknowledgement: This product includes software developed by Bill Paul. 4.Neither the name of the author nor the names of any co-contributors may be used to endorse or promote products derived from this software without specific prior written permission. THIS SOFTWARE IS PROVIDED BY Bill Paul AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL Bill Paul OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

## 13 The Network Time Protocol Version 4 Distribution Copyright Notice

The following copyright notice applies to all files collectively called the Network Time Protocol Version 4 Distribution. Unless specifically declared otherwise in an individual file, this notice applies as if the text was explicitly included in the file.

```
*****
*
* Copyright (c) David L. Mills 1992-2001
*
* Permission to use, copy, modify, and distribute this software and
* its documentation for any purpose and without fee is hereby
* granted, provided that the above copyright notice appears in all
* copies and that both the copyright notice and this permission
* notice appear in supporting documentation, and that the name
* University of Delaware not be used in advertising or publicity
* pertaining to distribution of the software without specific,
* written prior permission. The University of Delaware makes no
* representations about the suitability this software for any
* purpose. It is provided "as is" without express or implied
* warranty.
*
*****
```

14 OpenLDAP Public License  
Version 2.7, 7 September 2001

Redistribution and use of this software and associated documentation ("Software"), with or without modification, are permitted provided that the following conditions are met: 4.Redistributions of source code must retain copyright statements and notices, 5.Redistributions in binary form must reproduce applicable copyright statements and notices, this list of conditions, and the following disclaimer in the documentation and/or other materials provided with the distribution, and 6.Redistributions must contain a verbatim copy of this document. The OpenLDAP Foundation may revise this license from time to time. Each revision is distinguished by a version number. You may use this Software under terms of this license revision or under the terms of any subsequent revision of the license. THIS SOFTWARE IS PROVIDED BY THE OPENLDAP FOUNDATION AND ITS CONTRIBUTORS "AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OPENLDAP FOUNDATION, ITS CONTRIBUTORS, OR THE AUTHOR(S) OR OWNER(S) OF THE SOFTWARE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF

SUCH DAMAGE. The names of the authors and copyright holders must not be used in advertising or otherwise to promote the sale, use or other dealing in this Software without specific, written prior permission. Title to copyright in this Software shall at all times remain with copyright holders. OpenLDAP is a registered trademark of the OpenLDAP Foundation. Copyright 1999-2001 The OpenLDAP Foundation, Redwood City, California, USA. All Rights Reserved. Permission to copy and distribute verbatim copies of this document is granted.

## 15 OpenSSH License

The licenses which components of this software fall under are as follows. First, we will summarize and say that all components are under a BSD license, or a license more free than that. OpenSSH contains no GPL code. 1)Copyright (c) 1995 Tatu Ylonen <ylo@cs.hut.fi>, Espoo, Finland All rights reserved As far as I am concerned, the code I have written for this software can be used freely for any purpose. Any derived versions of this software must be clearly marked as such, and if the derived work is incompatible with the protocol description in the RFC file, it must be called by a name other than "ssh" or "Secure Shell". However, I am not implying to give any licenses to any patents or copyrights held by third parties, and the software includes parts that are not under my direct control. As far as I know, all included source code is used in accordance with the relevant license agreements and can be used freely for any purpose (the GNU license being the most restrictive); see below for details. [However, none of that term is relevant at this point in time. All of these restrictively licensed software components which he talks about have been removed from OpenSSH, i.e.

- RSA is no longer included, found in the OpenSSL library
- IDEA is no longer included, its use is deprecated
- DES is now external, in the OpenSSL library
- GMP is no longer used, and instead we call BN code from OpenSSL
- Zlib is now external, in a library
- The make-ssh-known-hosts script is no longer included
- TSS has been removed
- MD5 is now external, in the OpenSSL library
- RC4 support has been replaced with ARC4 support from OpenSSL
- Blowfish is now external, in the OpenSSL library

[The license continues] Note that any information and cryptographic algorithms used in this software are publicly available on the Internet and at any major bookstore, scientific library, and patent office worldwide. More information can be found e.g. at "<http://www.cs.hut.fi/crypto>". The legal status of this program is some combination of all these permissions and restrictions. Use only at your own responsibility. You will be responsible for any legal consequences yourself; I am not making any claims whether possessing or using this is legal or not in your country, and I am not taking any responsibility on your behalf.

## NO WARRANTY

BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

2)The 32-bit CRC implementation in `crc32.c` is due to Gary S. Brown. Comments in the file indicate it may be used for any purpose without restrictions: COPYRIGHT (C) 1986 Gary S. Brown. You may use this program, or code or tables extracted from it, as desired without restriction. 3)The 32-bit CRC compensation attack detector in `deattack.c` was contributed by CORE SDI S.A. under a BSD-style license. See <http://www.core-sdi.com/english/ssh/> for details. Cryptographic attack detector for `ssh` - source code Copyright (c) 1998 CORE SDI S.A., Buenos Aires, Argentina. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that this copyright notice is retained. THIS SOFTWARE IS PROVIDED "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES ARE DISCLAIMED. IN NO EVENT SHALL CORE SDI S.A. BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY OR CONSEQUENTIAL DAMAGES RESULTING FROM THE USE OR MISUSE OF THIS SOFTWARE. Ariel Futoransky [futo@core-sdi.com](mailto:futo@core-sdi.com) <<http://www.core-sdi.com>> 4) Remaining components of the software are provided under a standard 2-term BSD license with the following names as copyright holders: Markus Friedl Theo de Raadt Niels Provos Dug Song Aaron Campbell Doug Rabson Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: 1.Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. 2.Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. THIS SOFTWARE IS PROVIDED BY THE AUTHOR "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING,

BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

## 16 OpenSSL License LICENSE ISSUES

The OpenSSL toolkit stays under a dual license, i.e. both the conditions of the OpenSSL License and the original SSLeay license apply to the toolkit. See below for the actual license texts. Actually both licenses are BSD-style Open Source licenses. In case of any license issues related to OpenSSL please contact [openssl-core@openssl.org](mailto:openssl-core@openssl.org). Copyright (c) 1998-2002 The OpenSSL Project. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: 1.Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. 2.Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. 3.All advertising materials mentioning features or use of this software must display the following acknowledgment: "This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)" 4.The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact [openssl-core@openssl.org](mailto:openssl-core@openssl.org). 5.Products derived from this software may not be called "OpenSSL" nor may "OpenSSL" appear in their names without prior written permission of the OpenSSL Project. 6.Redistributions of any form whatsoever must retain the following acknowledgment: "This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>)" THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT "AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF

ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. This product includes cryptographic software written by Eric Young (eay@cryptsoft.com). This product includes software written by Tim Hudson (tjh@cryptsoft.com).

Original SSLeay License  
Copyright (C) 1995-1998 Eric Young (eay@cryptsoft.com)  
All rights reserved.

This package is an SSL implementation written by Eric Young (eay@cryptsoft.com).

The implementation was written so as to conform with Netscapes SSL. This library is free for commercial and non-commercial use as long as the following conditions are adhered to. The following conditions apply to all code found in this distribution, be it the RC4, RSA, lhash, DES, etc., code; not just the SSL code. The SSL documentation included with this distribution is covered by the same copyright terms except that the holder is Tim Hudson (tjh@cryptsoft.com). Copyright remains Eric Young's, and as such any Copyright notices in the code are not to be removed. If this package is used in a product, Eric Young should be given attribution as the author of the parts of the library used. This can be in the form of a textual message at program startup or in documentation (online or textual) provided with the package. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- 1.Redistributions of source code must retain the copyright notice, this list of conditions and the following disclaimer.
- 2.Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- 3.All advertising materials mentioning features or use of this software must display the following acknowledgement: "This product includes cryptographic software written by Eric Young (eay@cryptsoft.com)" The word 'cryptographic' can be left out if the routines from the library being used are not cryptographic related :-).
- 4.If you include any Windows specific code (or a derivative thereof) from the apps directory (application code) you must include an acknowledgement: "This product includes software written by Tim Hudson (tjh@cryptsoft.com)"

THIS SOFTWARE IS PROVIDED BY ERIC YOUNG "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. The license and distribution terms for any publically available version or derivative of this code cannot be changed. i.e. this code cannot simply be copied and put under another distribution license [including the GNU Public License.]

#### 17 TZFILE Header File Declaration

This file is in the public domain, so clarified as of June 5, 1996 by Arthur David Olson (arthur\_david\_olson@nih.gov).

#### 18 ZLIB Copyright Notice

(C) 1995-2002 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software. Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions: 1.The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required. 2.Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software. 3.This notice may not be removed or altered from any source distribution.

Jean-loup Gailly    Mark Adler  
jloup@gzip.org     madler@alumni.caltech.edu

#### 19 Sun RPC License

Sun RPC is a product of Sun Microsystems, Inc. and is provided for unrestricted use provided that this legend is included on all tape media and as a part of the software program in whole or part. Users may copy or modify Sun RPC without charge, but are not authorized to license or distribute it to anyone else except as part of a product or program developed by the user. SUN RPC IS PROVIDED AS IS WITH NO WARRANTIES OF ANY KIND INCLUDING THE WARRANTIES OF DESIGN, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, OR ARISING FROM A COURSE OF DEALING, USAGE OR TRADE PRACTICE. Sun RPC is provided with no support and without any obligation on the part of Sun Microsystems, Inc. to assist in its use, correction, modification or enhancement. SUN MICROSYSTEMS, INC. SHALL HAVE NO LIABILITY WITH RESPECT TO THE INFRINGEMENT OF COPYRIGHTS, TRADE SECRETS OR ANY PATENTS BY SUN RPC OR ANY PART THEREOF. In no event will Sun Microsystems, Inc. be liable for any lost revenue or profits or other special, indirect and consequential damages, even if Sun has been advised of the possibility of such damages. Sun Microsystems, Inc. 2550 Garcia Avenue Mountain View, California 94043 Copyright (c) 1988 by Sun Microsystems, Inc.

#### 20 Adaptec AIC SCSI Driver License

Copyright (c) 1994-2002 Justin T. Gibbs.

Copyright (c) 2000-2002 Adaptec Inc.

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: 1.Redistributions of source code must retain the above copyright notice, this list of conditions, and the following disclaimer, without modification. 2.Redistributions in binary form must reproduce at minimum a disclaimer substantially similar to the "NO WARRANTY"

disclaimer below ("Disclaimer") and any redistribution must be conditioned upon including a substantially similar Disclaimer requirement for further binary redistribution. 3. Neither the names of the above-listed copyright holders nor the names of any contributors may be used to endorse or promote products derived from this software without specific prior written permission. Alternatively, this software may be distributed under the terms of the GNU General Public License ("GPL") version 2 as published by the Free Software Foundation. NO WARRANTY THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDERS OR CONTRIBUTORS BE LIABLE FOR SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

21 QLogic 2300 License

Copyright (c) 1997, 1998, 1999, 2000, 2001 by Matthew Jacob

Feral Software

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: 1. Redistributions of source code must retain the above copyright notice immediately at the beginning of the file, without modification, this list of conditions, and the following disclaimer.

2. The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission. THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Inspiration and ideas about this driver are from Erik Moe's Linux driver (qlogicisp.c) and Dave Miller's SBus version of same (qlogicisp.c). Some ideas dredged from the Solaris driver.

## 22 QLogic SCSI License

Copyright (c) 1997, 1998 by Matthew Jacob

NASA/Ames Research Center All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: 1.Redistributions of source code must retain the above copyright notice immediately at the beginning of the file, without modification, this list of conditions, and the following disclaimer. 2.Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. 3.The name of the author may not be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Inspiration and ideas about this driver are from Erik Moe's Linux driver (qlogicisp.c) and Dave Miller's SBus version of same (qlogicisp.c). Some ideas dredged from the Solaris driver.

## 23 QLogic ISP 2300 Initiator/Target Firmware Copyright Notice

ISP2300 Initiator/Target Firmware  
with Fabric (Public Loop), Point-point, and  
expanded LUN addressing for FCTAPE

NOTICE

COPYRIGHT 2001 QLOGIC CORPORATION  
ALL RIGHTS RESERVED

This computer program is CONFIDENTIAL and contains TRADE SECRETS of QLOGIC CORPORATION. The receipt or possession of this program does not convey any rights to reproduce or disclose its contents, or to manufacture, use, or sell anything that it may describe, in whole or in part, without the specific written consent of QLOGIC CORPORATION. Any reproduction of this program without the express written consent of QLOGIC CORPORATION is a violation of the copyright laws and may subject you to civil liability and criminal prosecution.

Firmware Version 3.01.20 (15:30 Dec 19, 2002)

24 Intel Corporation EM Gigabit NIC Driver License

Copyright (c) 1999-2001 Intel Corporation

All rights reserved.

Redistribution and use in source and binary forms of the Software, with or without modification, are permitted provided that the following conditions are met:

1.Redistributions of source code of the Software may retain the above copyright notice, this list of conditions and the following disclaimer. 2.Redistributions in binary form of the Software may reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. 3.Neither the name of the Intel Corporation nor the names of its contributors shall be used to endorse or promote products derived from this Software without specific prior written permission. THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE INTEL OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

## 25 NIC Bonding Pseudo Device Driver

The bonding pseudo device driver contains various copyright statements:

1. Copyright 1999, Thomas Davis, tadavis@lbl.gov. Licensed under the GPL. Based on dummy.c, and eql.c devices. 2. Portions are (c) Copyright 1995 Simon "Guru Aleph-Null" Janes NCM: Network and Communications Management, Inc. BUT, I'm the one who modified it for ethernet, so: (c) Copyright 1999, Thomas Davis, tadavis@lbl.gov This software may be used and distributed according to the terms of the GNU Public License, incorporated herein by reference. 3. Author: Donald Becker becker@cesdis.gsfc.nasa.gov Copyright 1994-1996 Donald Becker This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation. The author may be reached as becker@CESDIS.gsfc.nasa.gov, or C/O Center of Excellence in Space Data and Information Sciences Code 930.5, Goddard Space Flight Center, Greenbelt MD 20771.

Documentation and source code may be found at  
<http://sourceforge.net/projects/bonding/>