

DSL300P

ADSL Modem Card

Easy Start

Read Me First

Version 0.71

- Windows® 95/98 Second Edition/98/Me/2000 are registered trademarks of Microsoft Corp.
- All other company or product names are trademarks or registered trademarks or service marks of their respective owners.

Product warranty does not apply to damage caused by lightning, power surges or wrong voltage usage.

About this Easy Start

This booklet contains information on setting up the ADSL modem card *DSL300P*. It touches on the key installation procedures to help you setup your modem in a breeze!

Installation Notes

- The graphics and screens illustrations shown in this easy start may differ from what you see from your system, but the steps still apply.
- A Philips Screwdriver is required for the card installation.
- The documentation for your computer should come in handy during the card installation. Have it ready by your side.
- It is recommended that any existing modem card be removed before installing your new modem card.

Safety Precaution


- Do not remove your card from its protective bag until you are ready to install it.
- Always try to hold your card by its edges. Avoid touching any electronic components on your card.
- Static electricity can cause permanent damage to your card. To prevent such a damage, you must ground yourself while installing the card:
 - » Use a grounding strap, which is a coiled wire with a clip at one end and an elastic strap at the other. Wear the strap around your wrist and attach the clip to any non-painted metal surface of the computer's chassis. OR
 - » If you do not have a grounding strap, touch any non-painted surface of the computer's chassis before you begin installation, and again every minute or so until the installation is completed.
- This product is for use only in UL Listed computers
- To reduce the risk of fire, use only No. 26 AWG or larger telecommunication line cord

Installing the Modem Card



Before you begin the following installation, ensure that you have powered off your computer and switched off the power! Disconnect any other devices connected to your computer, such as a telephone line connected to an existing modem.

1. After removing the cover of your computer, locate any available PCI-Bus slot and remove its cover plate. Save all the screws removed.
2. Insert the modem card firmly into the PCI-Bus slot.
3. Secure the modem card with the mounting screw.
4. Replace the cover of your computer and secure all the screws back in place.
5. Connect the power supply cord and power on your computer.




Connecting the Modem Card



The connection for the **Telephone Set** is **optional**. The **Phone Jack** provides convenience to users who share the same telephone point for the modem and the telephone set.

With this connection, a **Micro Filter** is needed between the **Phone Jack** and the **Telephone Set**.



Installing the Modem Drivers




Have the **Windows Installation CD** ready during installation, as it may be required.

There are 3 sets of drivers provided in the Installation CD. If you are using the **RFC1483** or **RFC 1577 protocol**, the drivers can be found in the **LAN** directory in the respective OS. If you are using the **RFC2364 protocol**, the drivers can be found in the **WAN** directory in the respective OS. **The following screen shots shows the RFC2364 protocol being used.**

Windows® Me

1. Power on your computer to start Windows. It will detect the newly-installed modem card and prompt for its drivers.




Select **Specify the location of the driver (Advanced)** option and then click **Next**. Place the **DSL300P Installation CD** into your CD-ROM drive.


2. Click **Specify a location**. For **RFC1483 or 1577 users**, browse to the **W2k98Me\Lan** folder on your CD-ROM drive. For **RFC2364 users**, browse to the **W2k98Me\Wan** folder on your CD-ROM drive. Click **Next**.




4. Click **Finish** when Windows has finished installing the driver.




5. Click **Yes** if prompted to restart your system.



3. Windows will prompt that the driver is found. Click **Next**.





6. After restarting, check that the drivers have been installed properly by right-clicking **My Computer** and selecting **Properties**. Click on the **Device Manager** tab.
7. If the drivers were not installed properly, a yellow exclamation mark will appear beside the installed device. In this case, uninstall the drivers before attempting another installation.
8. Proceed to set the Virtual Circuit Identification in order to establish an ADSL connection. Note that RFC1577 users need to refer to the **Configuring RFC1577** section to configure further.


Windows® 98/98 Second Edition (SE)

1. Power on your computer to start Windows. It will detect the newly-installed modem card and prompt for its drivers.

Place the **DSL300P Installation CD** into your CD-ROM drive and click **Next**.




Add New Hardware Wizard



2. Click the option "Search for the best driver for your device. (Recommended)." and click **Next**.

Add New Hardware Wizard




3. Select **Specify a location** and click **Browse...**

For RFC1483 or 1577 users, browse to the 'W2k98Me\Lan' directory on your CD-ROM and click OK.


For RFC2364 users, browse to the 'W2k98Me\Wan' directory on your CD-ROM and click OK.

Click **Next**.

Add New Hardware Wizard




Add New Hardware Wizard



4. Click **Next** again to proceed with installation of the driver found.
5. Click **Finish** when Windows has finished installing the driver.

6. When prompted for the Windows CD, remove the Installation CD in your CD-ROM drive and replace with your Windows CD.
7. Click **Yes** if prompted to restart your system.




8. After restarting, check that the drivers have been installed properly by right-clicking **My Computer** and selecting **Properties**. Click on the **Device Manager** tab.
 9. If the drivers were not installed properly, a yellow exclamation mark will appear beside the installed device. In this case, uninstall the drivers before attempting another installation.
10. Proceed to set the Virtual Circuit Identification in order to establish an ADSL connection. Note that RFC1577 users need to refer to the **Configuring RFC1577** section to configure further.

Windows® 95

1. Power on your computer to start Windows. It will detect the newly-installed modem card and prompt for its drivers.

Place the **DSL300P Installation CD** into your CD-ROM drive and click **Next**.



This wizard will complete the installation of:

PCI System Peripheral

by searching your local drives, network, and Internet locations for the most current driver.


If you have a disk or CD-ROM that came with this device, insert it now.

It is recommended that you let Windows search for an updated driver. To do this, click Next to continue.

< Back Next > Cancel

2. Click **Other Locations...** to direct Windows to the drivers.

3. For **RFC1483** or **1577** users, browse to the **Win95\Lan** folder on your CD-ROM. For **RFC2364** users, browse to the **Win95\Wan** folder on your CD-ROM. Click **OK**.



Type the name of the folder that contains the driver you want. To search for a folder, click Browse.

tion

D:\Win95\Wan

Browse...



driver for this

OK



Cancel

4. Windows will prompt that the driver is found. Click **Finish**.


5. If you are prompted to insert the Installation CD, click **OK**. Browse to the **Win95\WAN** or **Win95\LAN** folder on the CD-ROM, then click **OK**.



6. If you are prompted to insert Windows CD, replace the CD in the CD-ROM drive with the Windows CD and then click **OK**. Browse to the root directory of the CD-ROM, then click **OK**.




7. If there is a **Version Conflict** prompt about a file being copied is older, click **Yes** to keep your existing file.
8. Click **Yes** if prompted to restart.
9. After restarting, check that the drivers have been installed properly by right-clicking **My Computer** and selecting **Properties**. Click on the **Device Manager** tab.
10. If the drivers were not installed properly, a yellow exclamation mark will appear beside the installed device. In this case, uninstall the drivers before attempting another installation.
11. Proceed to set the Virtual Circuit Identification in order to establish an ADSL connection. Note that RFC1577 users need to refer to the **Configuring RFC1577** section to configure further.





Windows® 2000

1. Power on your computer to start Windows. It will detect the newly-installed modem card and prompt for its drivers.



2. Place the **DSL300P Installation CD** into your CD-ROM drive and click **Next**.

3. Select **"Search for a suitable driver for my device (recommended)"** and click **Next**.




4. Select **"Specify a location"** and click **Next**.

5. Click **Browse...**

For RFC1483 or 1577 users, browse to the 'W2k98Me\Lan' directory on your CD-ROM and click **OK**.


For RFC2364 users, browse to the 'W2k98Me\Wan' directory on your CD-ROM and click **OK**.



6. Windows will prompt that a driver has been found. Click **Next**. If prompted for the Installation CD, click **OK**.


7. A **Digital Signature Not Found** Window may appear. This is displayed due to different driver versions. Click **Yes**.

8. Click **Finish** when done.



9. A **Digital Signature Not Found** Window may appear again. Click **Yes**.

10. To verify that the drivers have been installed properly, right-click **My Computer** and select **Properties**. Click on the **Hardware** tab and then **Device Manager...** If the drivers were not installed properly, a yellow exclamation mark will appear beside the installed device. In this case, uninstall the drivers before attempting another installation.





11. Proceed to set the Virtual Circuit Identification in order to establish an ADSL connection. Note that RFC1577 users need to refer to the **Configuring RFC1577** section to configure further.

Monitoring the ADSL Line

To set the Virtual Path Identifier (VPI) and the Virtual Circuit Identifier (VCI) and monitor the ADSL line, double-click on the **DSL300P PCI ADSL Modem** icon in the **Control Panel** or from the system tray's icon near the clock at the bottom



right of the screen . If you open from the system tray, use **Alt-A** to reveal the toolbox and then click on **Advanced Monitoring**.



Under the **General** tab, the **ADSL Line Information** shows the status of the line. When the connection is established, information such as the number and rates of bytes received/transmitted are displayed.

Configuring RFC1577

For **RFC1577 users**, you have to change the encapsulation mode and configure the **TCP/IP Properties** from the **Protocol Setup** tab. Press **Alt+P** from the **ADSL Line Information** window. Click the **Protocol Setup** tab.

DSL300P PCI ADSL Modem

AutoLog | Connection | Line Setup | ATM Statistics | AAL Statistics
General | Physical Layer Statistics | ATM Link Statistics | AAL Link Statistics
Protocol Setup | ATM QAM Loopback | HAL Diagnostics | TCP/IP

ATM Virtual Circuit Identification

	Virtual Circuit 0	Virtual Circuit 1
Virtual Path Identifier (VPI)	0	8
Virtual Circuit Identifier (VCI)	101	43

Aggregate Channel Setup

Encapsulation Mode: Bridged IP over ATM

Maximum Packet Length

Receive: 1500

Transmit: 1500

Aggregate Channel Setup

Encapsulation Mode: Bridged IP over ATM LLC SNAP (RFC1483)
Bridged IP over ATM LLC SNAP (RFC1483)
Routed IP over ATM LLC SNAP (RFC1483)
Bridged IP over ATM VCMUX (RFC1483)
Routed IP over ATM VCMUX (RFC1483)
Classical IP over ATM (RFC1577)

Maximum Packet Length

Receive: 1500

Transmit: 1500

Apply



OK Cancel Help

Change the encapsulation mode from the **Bridged IP over ATM LLC SNAP (RFC1483)** to the **Classical IP over ATM (RFC1577)** from the **Encapsulation Mode** under the **Aggregate Channel Setup**. Click **Apply** and **OK** after changing.




You need to restart your system for the values to take effect!


Next, configure the TCP/IP Properties. From the Windows desktop, right-click on **Network Neighborhood** and select **Properties**. Search for the **TCP/IP -> DSL300P PCI ADSL Modem** and click the **Properties** button.



Select the **DNS Configuration** tab. Enter the values given by your ISP in the **Host** box and **DNS Server Search Order** box and click **Add**.

Next, under the **Gateway** tab, enter the **New Gateway** value and click **Add**.







Under the **IP Address** tab, specify the **IP Address** and **Subnet Mask** given by your ISP.


Click **OK**.

Click **OK** again and then **Yes** to restart.



Setting the Virtual Circuit Identification and Changing Encapsulation Mode


To set the Virtual Path Identifier (VPI) and the Virtual Connection Identifier (VCI), click the **Protocol Setup** tab. Set the values of the VPI's and VCI's Virtual Circuit 0 and then click **Apply** and **OK**.



You need to restart your system for the values to take effect!

Uninstalling the ADSL Modem Drivers in Windows® Me/98/98SE/95/2000

1. From your Windows taskbar, click **Start > Settings > Control Panel**. Double-click

the  (Add/Remove Programs) icon.

2. From the **Add/Remove Programs Properties** Window, under the **Install/Uninstall** tab, select **DSL300P PCI ADSL Modem** and click **Add/Remove...** .
3. Follow the instructions to start the uninstallation.
4. Click the **OK** button on the **Add/Remove Programs Properties** Window.
5. Restart your system.