States • ADSL	http://t.t.d.0.218xclad	han hea	M 🚺 Ge 1844 ^M Aborat Antine
AUSL Status AUSL Status AUSL Status AUSL Status AUSL Status AUX Configuration Aux		WAN Configuration	
Current line 1 KAN	+ ADSL Status	treat configuration	
UNION	Configuration	PVC Profile	
AAT Cons Sector Table Multic Cashbarration Fitneware Lipdate Protocol/Encopealation: Counterl Prove ATM VPI: 0 VPI: 0 VCI: 101 Bridge Fitnering Source Cathbarration Fitneware Lipdate Protocol/Encopealation: Counterl Prove ATM VPI: 0 VCI: 101 Bridge Fitnering Source Cathbarration Protocol/Encopealation: Counterl Prove ATM Protocol/Encopealation: Databarration VCI: 101 Bridge Fitnering Source Cathbarration Protocol/Encopealation: Counterl Prove ATM Protocol/Encopealation VCI: 101 Bridge Fitnering Source Cathbarration Protocol/Encopealation Counterl Prove ATM Protocol/Encopealation Protocol/Enc	+ 14N	Enable this profile? Yes	4
Cover Sector Table Multic Centimeration Firmeman Lipdate Prof. Centimeration Firmeman Lipdate Prof. Centimeration Cover Sector Centings Sindle Filtering Cover Centings Ta Normal Mude Ta Normal Mude Sector Centings Sindle Sindle The Sector State Cover Centings Cover Centings C	+ NAT	Protocol/Encepsulation: Onnie	cal Power ATM
Nucle Centranentien Firmewarn Lipdate Firmewarn Lipdate Pert Centranentien Firmewarn Lipdate Pert Centranentien Firmewarn Lipdate Pert Centranentien	· DVS	WPI: 0	
Firmmann Lipstein Bridge Made Enable† Desclied PPP configuration (optional) Description Source Setting: Provide Enable PPP configuration (optional) Username: Pessword: Auto reconnect from ISP offen there is no data transfer? Enable auto reconnect from ISP offen there is no data transfer? Enable source reconnect to 18P outon deconnect from ISP offen there is no data transfer? Enable source reconnect to 18P outon deconnect from ISP offen there is no data transfer? Enable source reconnect to 18P outon deconnect from ISP offen there is no data transfer? Enable source reconnect to 18P outon deconnect from ISP offen there is no data transfer? Enable PPP Helf Bridge mode? Deabled witan lauching with branser? Enable PPP Helf Bridge mode? Deabled witan lauching with branser? Enable PPP Helf Bridge mode? Deabled	+ Nhc Castagration	VCE: 101	
PPP configuration (optional) PPP configuration (optional) Unements: Password: Authorization:	+ Firessare Update	Bridge Mode Enable? Doubl	led m
Save Setting: Username: Pessword: Auto recensect when ADSL link down? Auto recensect when ADSL link down? Auto recensect when ADSL link down? Auto recensect from DP when there is no data transfer? Enable auto recorrect to ISP when lauching web braveser? Enable PPP Hell Bridge mode? Direbled # Static WAN configuration (optional) wan seconds (Maximum allow: 32767seconds)	• Part Fernarding	PPP configuration (optional)	
Ta Nerreel Mode Pessovoeil Auto reconnect when ADSL link down7 Auto reconnect from DiP offer there is no data transfer? Enable auto reconnect to ISP when lauching web browser? Enable PPP Hell Bridge mode? Disabled w Static WAX configuration (optional) waxs pratic 10 165. 91. 95. 110 165. 91. 95. 110	+ Save Settings	Usernerse:	
Authentikotion: Authentikotion: Auto Auto reconnect when ADSL link down? Auto reconnect from DP when there is no data transfer? Enable auto reconnect in ISP when lauching web browser? Enable PPP Hell Bridge mode? Disbled w Static WAX configuration (optional) water semareb by weing eld the selected imp.	A constant	Password:	
Auto reconnect when ADSL link down? Auto disconnect from ISP when there is no data transfer? Enable auto reconnect to ISP when lauching web brawser? Enable PPP Hell Bridge mode? Enable PPP Hell Bridge	La seminadore :	Authentication:	Auto 🗯
Auto disconnect from ISP when there is no data transfer? Enable auto recornect to ISP when lauching web browser? Enable PPP Hell Bridge mode? Enable PPP Hell Bridge mode? Btotic WAX configuration (optional) WAX Stratic Tel: 166, 91, 95, 175 riors commets in voting at the soluted ins.		Auto recensed when ADSL link down7	
Enable auto recomment to 15P when lauching with branser? Enable PPP Half Bridge mode? Static WAN configuration (optional) WAN Stratic 18 16E 91 95 175 16E 91 95 175		Auto disconnect from LSP when there is no data transfer?	a seconds (Maximum allow: 32767seconds)
Enable PPP Half Bridge model Enable PPP Half Bridge model Static WAS configuration (optional) Water senter term of the senter term		Enable auto reconnect to ISP when lauching web browser?	Disabled ·
Static WAX carfiguration (optional) WAX search and a search the selected law.		Enable PPP Half Bridge mode?	Disting H
with the selected items.		Static WAN configuration (optio	(lan
orders commands for working with the selected items.		MAAN SPARIN TEN 166, 51	46 110

e Ddit Hen Fanorites Teo	Se Hwip				4
1 · O · M	🚯 Direch 🛨 Pavori	es 💕 Ned	0 0.	🗟 🛯 - 🗔 🏟 🚳	
man anna la the state of the st	e las			- 🖸 Ge 114a	*
	-				
Status	Usemame:				
ADSL Status	Password:		-		
a ta sea a ta	Authentication:		Auto 😁		
THE	Auto reconnect when down?	ADSL link	2		
NAT	Auto disconnect from	Auto disconnect from ISP when		seconds (Maximum allow: 32767seconds)	
Drus Reste Table	Enable auto reconnect to 18P de Table when lauching web program?		Disabled *	natasi 👻	
Albe Configuration	Enable PPP Half Bridg	e mode?	Disabled M		
evente	Static WAN configurat	tion (option	(lan		
Port Fernarding Bridge Elitering	WAN Bletic IP:	165.21.3	15.173		
Save Settings	WAY Bubnet Mask	255.255	255.0		
a Nersel Mode	WAN Gebenney:	165.21.1	25.172		
	IGNP configuration (a	ptianal)			
	Enable IGMP?	Disabled	-		
	You are now at WAN profile: 1 💌 Petrieve				
	Submit Recet				
	Please ensure to click j	iave Setting	a for setting	s to take effect.	
7 2					C Direct
start 1 C A E P	Construction	and sound the	1011		A DECK MARK

Step 6: Under Static WAN configuration (optional), Key in the WAN Static IP and others WAN configuration (optional). Check with your ISP for more details.

Step 7: Click Submit.



Step 8: Click DNS.

Step 9: Select Auto Discovery + User Configured.

Step 10: Enter the Preferred and Alternate DNS server.

Step 11: Click Apply.

Step 12: Click Save Settings.

Step 13: Follow the instructions.