

HP-UX - Single Server FCAL

HSG80 – (2) Dual Controller Rackmount – (Active, Standby)

Step1 – Select RM – Choose one high bandwidth model.

ESA12000 High-bandwidth Base Model

Includes: Datacenter 41U cabinet/rack; 2 - 24 slot enclosures with five-shelf power supplies each (expandable to eight); 4 - Fibre Channel HSG80 six-channel controllers with 256 MB cache each (expandable to 512 MB each); 15-meter host-to-controller cable; power cord and documentation. Holds up to 48 drive, expandable to 72 drives per controller pair. Also includes GLMs.

Requires: (4) HSG80 ACS kits and one host platform kit for each platform type connected, host adapter(s), connectivity options, and disks to be ordered separately.

Options: *Optical hub(s), cables, UPS, 256MB cache*

Description	Compaq
ESA12000 Quad Cntrl	380620-001(Blue)
ESA12000 Quad Cntrl	380620-002(Opal)

Optional Expansion Cab

Tip: Dual enclosure expansion cabinet...chose two for max config matching the color above.

ESA12000 No Cntrl. Blue	380640-001
ESA12000 No Cntrl. Opal	380640-002

Redundant Power Options: Optional

Description	Compaq
<i>Tip: Choose three per BA370 enclosure</i>	
180 Watt Power supply	380565-B21
<i>Tip: Choose one per BA370 enclosure</i>	
AC Input Unit	380564-B21
<i>Tip: Order one per rack cab</i>	
PDU 60Hz	380582-001

Cache Upgrades – Optional

Note: 256 or 512MB supported only...four slots available for cache...all slots must be of like size DIMMS

Description	Compaq
<i>Tip: Add only one per controller (ESA12000 comes with 256 MB per HSG80 Controller)</i>	
256MB – 2x128MB	380674-B21

Step2 – ACS – Firmware (PCMCIA) Card

Tip: One per HSG80 required.

Description	Compaq
ACS v8.3	380577-001

Step3 – Platform Kit

Note: Includes SWCC

Tip: One per OS type required

Description	Compaq
-------------	--------

HP-UX

380557-001

Step4 – Host Adapter

Note: GLM included

Tip: Only one adapter is required.

Description	Compaq
A3404A (HSC bus, K-Class)	(Must Be Ordered From Manufacturer)
A3591A (HSC bus, D-Class)	(Must Be Ordered From Manufacturer)

Step5 - Disks

Description	Compaq
4GB, 7200 RPM, UWSE	380691-B21
9GB, 7200 RPM, UWSE	DS-RZ1DA-VW
9GB, 10K RPM, UWSE	380588-B21
18GB, 7200 RPM, UWSE	DS-RZ1EA-VW
18GB, 10K RPM, UWSE	380589-B21

Step6 – Hub, GBIC's and Cables

Note: One Hub required...point to point not supported...(no GBIC's included)

HUB

Description	Compaq
12 Port Hub	295573-B22

GBIC and Connection Kit

Tip: Configure three for this config.

Description	Compaq
3 GBIC + 2 – 2M Cables	380579-B21

CABLES - Optional

Tip: One 5M cable/controller comes with RA8000 and two 2M cables come with the GBIC Kit.

Note: Order two 2Meter Cable to complete this config.

Description	Compaq
2Meter	234457-B21
5Meter	234457-B22
15Meter	234457-B23
30Meter	234457-B24
50Meter	234457-B25

Step7 – UPS

Description	Compaq
Low Voltage R3000	242705-001

Note: Actual VA is 2880...uses L5-30P plug

High Voltage R3000h	242705-003
---------------------	------------

Note: Actual VA is 3000...uses L6-20P plug